

FORM PTO-1390 (Modified) (REV 11-98)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER 28569.5100
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR To Be Assigned <b>09/486864</b>
INTERNATIONAL APPLICATION NO. PCT/JP98/04471	INTERNATIONAL FILING DATE 02 October 1998 (02.10.98)	PRIORITY DATE CLAIMED 23 October 97 (23.10.97)	
TITLE OF INVENTION SOUND-AMPLIFICATION APPARATUS			
APPLICANT(S) FOR DO/EO/US Isao KAKUHARI, Kenichi TERAJ, and Hiroyuki HASHIMOTO			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
<ol style="list-style-type: none"> <li>1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>3. <input type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).</li> <li>4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.</li> <li>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau).</li> <li>b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau.</li> <li>c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).</li> </ol> </li> <li>6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)).</li> <li>7. <input checked="" type="checkbox"/> A copy of the International Search Report (PCT/ISA/210).</li> <li>8. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau).</li> <li>b. <input type="checkbox"/> have been transmitted by the International Bureau.</li> <li>c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired.</li> <li>d. <input checked="" type="checkbox"/> have not been made and will not be made.</li> </ol> </li> <li>9. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).</li> <li>10. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).</li> <li>11. <input checked="" type="checkbox"/> A copy of the International Preliminary Examination Report (PCT/IPEA/409).</li> <li>12. <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).</li> </ol>			
Items 13 to 20 below concern document(s) or information included:			
<ol style="list-style-type: none"> <li>13. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.</li> <li>14. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</li> <li>15. <input type="checkbox"/> A <b>FIRST</b> preliminary amendment.</li> <li>16. <input type="checkbox"/> A <b>SECOND</b> or <b>SUBSEQUENT</b> preliminary amendment.</li> <li>17. <input type="checkbox"/> A substitute specification.</li> <li>18. <input type="checkbox"/> A change of power of attorney and/or address letter.</li> <li>19. <input checked="" type="checkbox"/> Certificate of Mailing by Express Mail</li> <li>20. <input type="checkbox"/> Other items or information:</li> </ol>			

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.486) <b>To the Assignee</b> <b>09/486864</b>		INTERNATIONAL APPLICATION NO. <b>PCT/JP98/04471</b>		ATTORNEY'S DOCKET NUMBER <b>28569.5100</b>	
----------------------------------------------------------------------------------------------	--	--------------------------------------------------------	--	-----------------------------------------------	--

21. The following fees are submitted:

**BASIC NATIONAL FEE ( 37 CFR 1.492 (a) (1) - (5) ) :**

<input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO .....	<b>\$970.00</b>
<input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO .....	<b>\$840.00</b>
<input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO .....	<b>\$690.00</b>
<input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) .....	<b>\$670.00</b>
<input type="checkbox"/> International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) .....	<b>\$96.00</b>

**ENTER APPROPRIATE BASIC FEE AMOUNT =**

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	33 - 20 =	13	x \$18.00		<b>\$234.00</b>
Independent claims	3 - 3 =	0	x \$78.00		<b>\$0.00</b>
Multiple Dependent Claims (check if applicable). <input type="checkbox"/>					<b>\$0.00</b>
<b>TOTAL OF ABOVE CALCULATIONS =</b>					<b>\$1,074.00</b>
Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). <input type="checkbox"/>					<b>\$0.00</b>
<b>SUBTOTAL =</b>					<b>\$1,074.00</b>
Processing fee of <b>\$130.00</b> for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).					<b>\$0.00</b>
<b>TOTAL NATIONAL FEE =</b>					<b>\$1,074.00</b>
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). <input type="checkbox"/>					<b>\$0.00</b>
<b>TOTAL FEES ENCLOSED =</b>					<b>\$1,074.00</b>
					<b>Amount to be: refunded \$</b>
					<b>charged \$</b>

**CALCULATIONS PTO USE ONLY**

☒ A check in the amount of **\$1,204.00** to cover the above fees is enclosed.


☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \_\_\_\_\_ to cover the above fees.  
A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **19-2814** A duplicate copy of this sheet is enclosed.

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:

**Michael K. Kelly, Reg. No. 32,848**  
**SNELL & WILMER**  
 One Arizona Center  
 400 E. Van Buren Street  
 Phoenix, AZ 85004-2202  
 P: (602) 382-6291  
 F: (602) 382-6070



SIGNATURE

**Michael K. Kelly**

NAME

**32,848**

REGISTRATION NUMBER

**March 2, 2000**

DATE

28/PRTS

09/486864  
514 Rec'd PCT/PTO 02 MAR 2000

P17053

- 1 -

## DESCRIPTION

### SOUND-AMPLIFICATION APPARATUS

#### 5 TECHNICAL FIELD

The present invention relates to a sound-amplification apparatus for outputting an amplified sound having an intended directionality using an active directionality control.

10

#### BACKGROUND ART

Conventionally, a horn loudspeaker system has been used for increasing the directionality of an amplified sound. Such a conventional sound-amplification apparatus will be described with reference to Figure 1.

15

A conventional horn loudspeaker system 20 illustrated in Figure 1 includes a horn driver 21 and a horn 22 for controlling the acoustic radiation direction and the directionality angle. The horn 22 is an acoustic tube for forwardly radiating an amplified sound by the horn acoustic radiation plane 23. In the figure,  $i$  is the diameter of the horn acoustic radiation plane 23, and  $k$  is an arrow denoting the direction in which a sound travels through the horn 22.

20

25

In order to narrow the directionality angle, it is generally necessary to increase the diameter  $i$  of the horn acoustic radiation plane 23. Moreover, in order to reduce the disturbance in the sound pressure frequency characteristic of a sound to be radiated, it is necessary to reduce the frequency change in the

30

008050-4929460

acoustic impedance of the horn 22 along the axis thereof. Therefore, in the horn 22 of Figure 1, the cross section thereof along a direction perpendicular to the sound wave traveling direction  $k$  is varied continuously and smoothly. A sound wave reproduced by the horn driver 21 is externally radiated through the horn acoustic radiation plane 23, with its directionality being controlled while it is guided through the horn 22 along the direction of the arrow  $k$ .

10

With the above-described conventional sound-amplification apparatus 20, however, it is necessary to increase the horn acoustic radiation plane 23 in order to obtain a narrow directionality. Moreover, the directional radiation pattern of an amplified sound to be radiated is uniquely determined by the shape of the horn 22. Therefore, it is necessary to replace the horn 22 with another depending upon the required directional radiation pattern.

20

On the other hand, the reproduction of an acoustic signal should preferably be performed with a desirable S/N ratio even in environmental noise. Therefore, a directional loudspeaker apparatus using an ellipsoidal acoustic reflector has been proposed in the art. Such a conventional example will be described below with reference to figures.

25

Figure 2 is a structure diagram illustrating a conventional directional loudspeaker apparatus 30 illustrated in Japanese Laid-Open Publication No. 2-87797.

30

09485864-050800

The directional loudspeaker apparatus 30 includes a concave (parabolic) reflector 31, and a sound source 32 which is provided within the reflector 31 to face a central portion thereof. In this way, a sound output from the sound source 32 is reflected by the reflector 31 so that a sound having a strong directionality along the axis of the reflector 31 is output on the rear side of the sound source 32.

10

Figure 3 is a structure diagram illustrating another conventional directional loudspeaker apparatus 40 illustrated in Japanese Laid-Open Publication No. 8-228394.

15

The directional loudspeaker apparatus 40 includes a concave (hemispherical) reflector 41, and a sound source 42 which is provided within the reflector 41 to face a central portion thereof. The sound source 42 and the reflector 41 are kept at a constant interval, and a rear cover 43 is attached on the rear side of the sound source 42. By covering the rear side of the sound source 42 with the rear cover 43, a rearward sound radiated directly from the sound source 42 is reduced. In this way, the divergent component is reduced, thereby further emphasizing the directional radiation pattern given by the reflected sound from the reflector 41.

30

In the conventional directional loudspeaker apparatus 30 illustrated in Figure 2, sound radiation also occurs from the rear side of the sound source 32, whereby the sound is scattered about the sound

source 32. Therefore, it is difficult to obtain a narrow directional radiation pattern. In the conventional directional loudspeaker apparatus 40 illustrated in Figure 3, a rear cover 43 of a sound absorbing material or a sound blocking material is provided in order to reduce the sound radiation from the rear side of the sound source 42. In practice, however, it is difficult to reduce the radiated sound except for very high frequencies.

An on-vehicle sound-amplification apparatus has been one application of such a sound-amplification apparatus. For such a conventional on-vehicle sound-amplification apparatus, a horn loudspeaker system is typically employed in order to efficiently diffuse a reproduced sound to the environment. A conventional on-vehicle sound-amplification apparatus 50 will be described below with reference to Figure 4.

In Figure 4, reference numeral 34 denotes a horn driver, 35 a reentrant horn for controlling the acoustic radiation main axis and the directionality angle, 36 a horn acoustic radiation plane,  $l$  the diameter of the horn acoustic radiation plane,  $j$  the horn length, and  $k$  and  $k'$  each denote a horn central axis. Generally, the narrower the directionality angle is, the larger the diameter  $l$  of the horn acoustic radiation plane 36 is. In order to obtain a desirable sound pressure frequency characteristic, it is necessary to increase the length of each of the horn central axes  $k$  and  $k'$ . However, the horn driver 34 and the horn acoustic radiation plane 36 are coupled together with the reentrant horn 35, which is obtained

by folding back a horn, so as to reduce the horn length  $j$  without reducing the length of the horn central axes  $k$  and  $k'$ .

5           In the conventional on-vehicle sound-amplification apparatus 50 having such a structure, a sound wave reproduced by the horn driver 34 is externally radiated through the horn acoustic radiation plane 36, with its directionality being controlled  
10 while it is guided through the reentrant horn 35 in the directions indicated by the arrows along the horn central axes  $k$  and  $k'$ .

15           In the above-described conventional on-vehicle sound-amplification apparatus 50, it is necessary to increase the horn acoustic radiation plane 36 in order to obtain a narrow directionality. In practice, however, it is difficult to increase the horn acoustic radiation plane 36 because it is provided on the outside of the  
20 vehicle body. Therefore, it is difficult to avoid the use of a small-diameter horn loudspeaker system, resulting in a wide directional radiation pattern. Therefore, the radiated sound is transferred to the passengers including the driver, thereby hindering them  
25 from having a conversation or listening to the radio.

#### DISCLOSURE OF THE INVENTION

30           A sound-amplification apparatus according to the present invention includes an acoustic signal source for outputting an acoustic signal; an amplified sound source for receiving the acoustic signal from the acoustic signal source and radiating an amplified sound; a control sound source provided in the vicinity

003090" 49898460

of the amplified sound source for radiating a control sound; and signal processing means for producing a control sound signal by controlling at least one of an amplitude and a phase of the acoustic signal from the acoustic signal source so that an acoustic space having a desired directionality is formed by interference between the amplified sound and the control sound, and providing the control sound signal to the control sound source.

10

In one embodiment, the signal processing means includes an error detector provided in the vicinity of the control sound source for detecting a synthesized sound between the amplified sound and the control sound; directional radiation pattern selection means for selecting one of an output from the error detector and the acoustic signal from the acoustic signal source so as to obtain a predetermined directional radiation pattern; and calculation means for producing the control sound signal by using the signal selected by the directional radiation pattern selection means, and providing the control sound signal to the control sound source, wherein the calculation means is provided for: when ensuring a directionality such that the amplified sound directed toward the error detector is reduced, producing, as a first control sound signal, a signal obtained by controlling the amplitude and the phase of the acoustic signal from the acoustic signal source so that the output signal from the error detector is 0; when ensuring a dipole directional radiation pattern, producing, as a second control sound signal, a signal obtained by inverting the phase of the acoustic signal from the acoustic signal source; when ensuring a non-

15

20

25

30

09486864 "060800



directional radiation pattern, producing, as a third control sound signal, a signal having the same phase as that of the acoustic signal from the acoustic signal source; and providing one of the first to third control sound signals to the control sound source as the control sound signal.

The control sound source may be provided along the same axis with the amplified sound source so that an acoustic radiation plane thereof is located symmetrically with an acoustic radiation plane of the amplified sound source.

The error detector may be provided along a straight line which passes through respective centers of the acoustic radiation planes of the amplified sound source and the control sound source.

In one embodiment, the calculation means includes: a filtered-X filter for, where a transfer function of a space extending from the control sound source to the error detector is denoted by  $C$ , multiplying the acoustic signal output from the acoustic signal source by the transfer function  $C$ ; an adaptive filter for performing a convolution calculation on the acoustic signal from the acoustic signal source with a transfer function  $F$ , and providing the obtained calculation result to the control sound source as the first control sound signal; and a coefficient updatator for receiving an output from the directional radiation pattern selection means as an error signal, receiving an output from the filtered-X filter as a reference signal, updating a coefficient of

00880800-060800

the adaptive filter so that the error signal is small, and optimizing the transfer function F.

5 The amplified sound source may include: a horn driver for converting the acoustic signal from the acoustic signal source to an aerial vibration; and a horn-shaped acoustic tube for continuously enlarging a wavefront of the aerial vibration output from the horn driver along a sound wave traveling direction.

10

The control sound source may include: a horn driver for converting the control sound signal output from the signal processing means to an aerial vibration; and a horn-shaped acoustic tube for continuously enlarging a wavefront of the aerial vibration output from the horn driver along a sound wave traveling direction.

15

The acoustic tube may include a horn which is folded back at least once. Preferably, the number of times the acoustic tube is folded back is an odd number.

20

An acoustic radiation plane of the amplification-sound apparatus and an acoustic radiation plane of the control sound source may be placed such that the difference between the phase of the amplified sound and the phase of the control sound in a desired frequency are substantially within the angle of  $90^\circ$  with respect to the main axis direction of acoustic radiation of the amplified sound.

25

30

According to another aspect of the present invention, the sound-amplification apparatus includes:

a concave reflector; and a sound source provided within the reflector so as to be unidirectional toward a center of the reflector.

5           In one embodiment, the sound source includes a control sound source for outputting a control sound and an amplified sound source for outputting an amplified sound, and further includes an acoustic signal source for outputting an acoustic signal; signal processing  
10 means for producing a control sound signal by controlling at least one of an amplitude and a phase of the acoustic signal from the acoustic signal source so that an acoustic space having a desired directionality is formed by interference between the amplified sound  
15 and the control sound, and providing the control sound signal to the control sound source.

          In one embodiment, the signal processing means includes: an error detector provided in a radiation  
20 space of the control sound from the control sound source for detecting a synthesized sound between the amplified sound and the control sound; a filtered-X filter for, where a transfer function of an acoustic space extending from the control sound source to the  
25 error detector is denoted by  $C$ , multiplying the acoustic signal output from the acoustic signal source by the transfer function  $C$ ; an adaptive filter for performing a convolution calculation on the acoustic signal from the acoustic signal source with a transfer  
30 function  $F$ , and providing the calculation result to the control sound source as the control sound signal; and a coefficient updatator for receiving an output from the error detector as an error signal, receiving an output

09486864-060800

from the filtered-X filter as a reference signal, updating a coefficient of the adaptive filter so that the error signal is small, and optimizing the transfer function F.

5

10 The sound-amplification apparatus further may include signal correction means for performing at least one of a delay control, an amplitude control and a phase control on the acoustic signal output from the acoustic signal source, and providing a resultant signal to the amplified sound source. In such a case, the signal processing means may include: an error detector provided in a radiation space of the control sound from the control sound source for detecting a synthesized sound between the amplified sound and the control sound; a filtered-X filter for, where a transfer function of an acoustic space extending from the control sound source to the error detector is denoted by C, multiplying the acoustic signal output from the acoustic signal source by the transfer function C; an adaptive filter for performing a convolution calculation on the acoustic signal from the acoustic signal source with a transfer function F, and providing the calculation result to the control sound source as the control sound signal; and a coefficient updatator for receiving an output from the error detector as an error signal, receiving an output from the filtered-X filter as a reference signal, updating a coefficient of the adaptive filter so that the error signal is small, and optimizing the transfer function F, wherein: where the delay control may be performed, the signal correction means performs the delay control with a delay time which corresponds to an amount of time

25

30

00486864 060000

required for the control sound radiated from the control sound source to reach the error detector. The transfer function  $F$  of the adaptive filter may be expressed as  $-G/C$ , where  $G$  denotes an acoustic transfer function from the amplified sound source to the error detector.

The control sound source may be provided along a same axis with the amplified sound source so that an acoustic radiation plane thereof is located symmetrically with an acoustic radiation plane of the amplified sound source.

The error detector may be provided along a straight line which passes through respective centers of the acoustic radiation planes of the amplified sound source and the control sound source.

An acoustic radiation plane of the amplification-sound source and an acoustic radiation plane of the control sound source may be placed such that the difference between the phase of the amplified sound and the phase of the control sound in a desired frequency are substantially within the angle of  $90^\circ$  with respect to the main axis direction of acoustic radiation of the amplified sound.

According to still another aspect of the present invention, an on-vehicle sound-amplification apparatus includes: a dipole sound source provided in the vicinity of a position of a passenger wherein at least one acoustic radiation axis thereof is directed outwardly from a vehicle interior; and signal

09486864-060800

processing means for amplifying an acoustic signal and then inputting an output thereof to the dipole sound source.

5           In one embodiment, the on-vehicle sound-amplification apparatus further includes: a non-directional sound source provided in the vicinity of a center of the dipole sound source wherein an acoustic radiation thereof is driven to have an inverted phase  
10           from that of the acoustic radiation of the dipole sound source which is directed into the vehicle interior, wherein the output from the signal processing means is also input to the non-directional sound source.

15           In one embodiment, the dipole sound source includes at least two loudspeakers wherein the at least two loudspeakers are arranged so that respective acoustic radiation planes thereof are directed opposite to each other; and the signal processing means variably  
20           controls the phase of an input to at least one of the loudspeakers included in the dipole sound source.

25           For example, each of the at least two loudspeakers included in the dipole sound source has an acoustic tube whose cross-sectional area along a direction perpendicular to a sound wave traveling direction varies continuously; the acoustic tubes of the respective loudspeakers are arranged so that  
30           respective acoustic radiation planes thereof are directed opposite to each other; and a radiated sound from the loudspeaker which is driven by an output from the signal processing means is radiated by being guided along the acoustic tube.

09486864.060800

09486864 "060800

In one embodiment, the signal processing means includes: a radiation sound detector provided in the vicinity of a first one of the at least two  
5 loudspeakers included in the dipole sound source; an error detector provided in the vicinity of a second one of the loudspeakers included in the dipole sound source; an adder for adding together respective outputs from the radiated sound detector and the error  
10 detector; and calculation means for receiving the acoustic signal and the output from the adder, performing a calculation so that the output from the adder is small, and inputting the obtained result to the second loudspeaker located in the vicinity of the  
15 error detector, wherein the acoustic signal is input to the first loudspeaker located in the vicinity of the radiated sound detector.

In such a case, for example, the calculation  
20 means includes: an adaptive filter for receiving the acoustic signal; a filter for receiving the acoustic signal; and a coefficient updator for receiving the output from the adder and an output from the filter, wherein: an output from the adaptive filter is input to  
25 the second loudspeaker located in the vicinity of the error detector; the coefficient updator updates a coefficient of the adaptive filter by performing a calculation so that the output from the adder is small, and the filter has a characteristic equal to a transfer  
30 function from the error detector to the second loudspeaker located in the vicinity of the error detector.

000000"4989460

In another embodiment, the signal processing means includes: a radiated sound detector arranged in the vicinity of a first one of the at least two loudspeakers included in the dipole sound source; a  
5 first error detector arranged in the vicinity of a second one of the loudspeakers included in the dipole sound source; a second error detector arranged in the vicinity of the non-directional sound source; signal correction means for receiving an output from the  
10 second error detector; a first adder for adding together an output from the radiation sound detector and an output from the first error detector; a second adder for adding together the output from the first error detector and an output from the signal correction means; first calculation means for receiving the  
15 acoustic signal and an output signal from the first adder, and performing a calculation so that the output signal from the first adder is small, wherein an output therefrom is input to the second loudspeaker located in the vicinity of the first error detector; and second  
20 calculation means for receiving the acoustic signal and an output signal from the second adder, and performing a calculation so that the output signal from the second adder is small, wherein an output therefrom is input to the non-directional sound source, wherein the acoustic  
25 signal is input to the first loudspeaker located in the vicinity of the radiation sound detector.

In such a case, for example, the first  
30 calculation means includes: a first adaptive filter for receiving the acoustic signal; a first filter for receiving the acoustic signal; and a first coefficient updatator for receiving the output from the first adder



and an output from the first filter, wherein: an output from the first adaptive filter is input to the second loudspeaker located in the vicinity of the first error detector; the first coefficient updatator updates a coefficient of the first adaptive filter by performing a calculation so that the output from the first adder is small; and the first filter has a characteristic equal to a transfer function from the first error detector to the second loudspeaker located in the vicinity of the first error detector, the second calculation means includes: a second adaptive filter for receiving the acoustic signal; a second filter for receiving the acoustic signal; and a second coefficient updatator for receiving the output from the second adder and an output from the second filter, wherein: an output from the second adaptive filter is input to the non-directional sound source; the second coefficient updatator updates a coefficient of the second adaptive filter by performing a calculation so that the output from the second adder is small; and the second filter has a characteristic equal to a transfer function from the second error detector to the non-directional sound source.

The acoustic tube of each of the at least two loudspeakers included in the dipole sound source may be formed of a sound path having a desired bent shape.

Preferably, the at least two loudspeakers included in the dipole sound source are arranged so that an interval between the respective acoustic radiation planes included in the acoustic tubes of the loudspeakers is less than or equal to approximately  $1/2$

of the wavelength of the reproduced sound.

5 The dipole sound source may include an amplified  
sound source for radiating an amplified sound and a  
control sound source for radiating a control sound,  
wherein an acoustic radiation plane of the amplified  
sound source and an acoustic radiation plane of the  
control sound source may be placed such that the  
10 difference between the phase of the amplified sound and  
the phase of the control sound in a desired frequency  
are substantially within the angle of  $90^\circ$  with respect  
to the main axis direction of acoustic radiation of the  
amplified sound.

15 Therefore, the present invention has objectives  
of: (1) providing a sound-amplification realizing a  
plurality of directionalities from a narrow directional  
radiation pattern to a wide directional radiation  
pattern by signal processing without having to  
20 extensively change the structure of the loudspeaker  
system; (2) providing a directional loudspeaker  
apparatus as an amplification-sound apparatus  
implementing a sharp directional radiation pattern with  
a reflector by reducing a radiated sound from the back  
25 of the sound source; and (3) providing an on-vehicle  
amplification-sound apparatus in which a narrow  
directional radiation pattern is realized using any of  
amplification-sound apparatuses described above without  
making the size greater and a radiated sound  
30 transmitted to a driver and passengers is reduced.

These and other advantages of the present  
invention will become apparent to those skilled in the

094436364 060800

art upon reading and understanding the following detailed description with reference to the accompanying figures.

5 BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a diagram schematically illustrating a conventional amplification-sound apparatus.

Figure 2 is a diagram schematically illustrating  
10 a structure of a conventional directional loudspeaker  
apparatus.

Figure 3 is a diagram schematically illustrating a structure of another conventional directional  
15 loudspeaker apparatus.

Figure 4 is a vertical-sectional view schematically illustrating a conventional on-vehicle sound-amplification apparatus.

Figure 5 is a diagram schematically illustrating a structure of a sound-amplification apparatus of Embodiment 1 of the present invention.

25            Figure 6 is a block diagram illustrating signal processing means which is used in the sound-amplification apparatus of Embodiment 2 of the present invention.

30                    Figure 7A through 7E are signal waveform  
diagrams illustrating an operation of the  
amplification-sound apparatus shown in Figure 6.

Figure 8 is a diagram schematically illustrating a part of a structure of an amplification-sound apparatus of Embodiment 3 of the present invention.

5           Figure 9 is a diagram schematically illustrating a part of a structure of an amplification-sound apparatus of Embodiment 4 of the present invention.

10           Figure 10 is a diagram illustrating a directional radiation pattern of the amplification-sound apparatus shown in Figure 9.

15           Figure 11 is a block diagram illustrating calculation means which is used in the sound-amplification apparatus of Embodiment 5 of the present invention.

20           Figure 12 is a diagram schematically illustrating a part of a structure of an amplification-sound apparatus of Embodiment 6 of the present invention.

25           Figure 13 is a diagram schematically illustrating a part of a structure of an amplification-sound apparatus of Embodiment 7 of the present invention.

30           Figure 14 is a diagram schematically illustrating a part of another structure of an amplification-sound apparatus of Embodiment 7 of the present invention.

Figure 15 is a diagram schematically

09486664-060300

illustrating a part of a structure of an amplification-sound apparatus of Embodiment 7 of the present invention.

5           Figure 16 is a diagram schematically illustrating a structure of a directional loudspeaker apparatus of Embodiment 8 of the present invention.

10           Figure 17A shows a simulated sound pressure distribution of an amplified sound radiated from a conventional directional loudspeaker apparatus.

15           Figure 17B shows a simulated sound pressure distribution of an amplified sound radiated from the directional loudspeaker apparatus shown in Figure 16.

            Figure 17C shows a gauge for the sound pressure shown in Figure 17A and 17B.

20           Figure 18 is a diagram schematically illustrating a structure of a directional loudspeaker apparatus of Embodiment 9 of the present invention.

25           Figure 19 is a diagram schematically illustrating a structure of a directional loudspeaker apparatus of Embodiment 10 of the present invention.

30           Figure 20 is a diagram schematically illustrating a structure of a directional loudspeaker apparatus of Embodiment 11 of the present invention.

            Figure 21 is a diagram schematically illustrating a part of a structure of a directional

09485854-060300

loudspeaker apparatus of Embodiment 12 of the present invention.

Figure 22 is a diagram schematically illustrating a structure of a directional loudspeaker apparatus of Embodiment 13 of the present invention.

Figure 23 is a diagram schematically illustrating a structure of an on-vehicle amplification-sound apparatus of Embodiment 14 of the present invention as applied to a truck-type vehicle.

Figure 24 is a block diagram illustrating an electric circuit in the apparatus structure shown in Figure 23.

Figure 25 is a diagram schematically illustrating a structure of an on-vehicle amplification-sound apparatus of Embodiment 15 of the present invention as applied to a truck-type vehicle.

Figure 26 is a block diagram illustrating an electric circuit in the apparatus structure shown in Figure 25.

Figure 27 is a block diagram illustrating an electric circuit in the structure of an on-vehicle amplification-sound apparatus of Embodiment 16 of the present invention as applied to a truck-type vehicle.

Figure 28A is a diagram illustrating the results of a simulation based on a boundary element method for a directional radiation pattern obtained when the phase

difference between two loudspeakers included in an on-vehicle amplification-sound apparatus according to Embodiment 16 of the present invention is  $180^{\circ}$ .

5           Figure 28B is a diagram illustrating the results of a simulation based on a boundary element method for a directional radiation pattern obtained when the phase difference between two loudspeakers included in an on-vehicle amplification-sound apparatus according to  
10           Embodiment 16 of the present invention is  $150^{\circ}$ .

          Figure 28C is a diagram illustrating the results of a simulation based on a boundary element method for a directional radiation pattern obtained when the phase  
15           difference between two loudspeakers included in an on-vehicle amplification-sound apparatus according to Embodiment 16 of the present invention is  $120^{\circ}$ .

          Figure 28D a diagram illustrating the results of a simulation based on a boundary element method for a directional radiation pattern obtained when the phase  
20           difference between two loudspeakers included in an on-vehicle amplification-sound apparatus according to Embodiment 16 of the present invention is  $90^{\circ}$ .

25           Figure 29 is a block diagram illustrating a sound source structure of an on-vehicle amplification-sound apparatus of Embodiment 17 of the present invention and an electric circuit thereof.

30           Figure 30 is a block diagram illustrating a sound source structure of an on-vehicle amplification-sound apparatus of Embodiment 18 of the present

09486864.060800

invention and an electric circuit thereof.

5           Figure 31 is a block diagram illustrating a sound source structure of an on-vehicle amplification-sound apparatus of Embodiment 19 of the present invention and an electric circuit thereof.

10           Figure 32 is a block diagram illustrating a sound source structure of an on-vehicle amplification-sound apparatus of Embodiment 20 of the present invention and an electric circuit thereof.

15           Figure 33 is a block diagram illustrating a sound source structure of an on-vehicle amplification-sound apparatus of Embodiment 21 of the present invention and an electric circuit thereof.

20           Figure 34A is a vertical-sectional view of the acoustic tube included in an on-vehicle amplification-sound apparatus of Embodiment 22 of the present invention.

25           Figure 34B is a horizontal-sectional view of an acoustic tube included in the on-vehicle amplification-sound apparatus of Embodiment 22 of the present invention.

30           Figure 35A is a diagram illustrating a boundary element method simulation result of a directional radiation pattern obtained when the interval between the acoustic radiation planes of two loudspeakers included in an on-vehicle amplification-sound apparatus of Embodiment 23 of the present invention is 1/4 of the

008090"49898460



wavelength of the reproduced sound.

5        Figure 35B a diagram illustrating a boundary  
element method simulation result of a directional  
radiation pattern obtained when the interval between  
the acoustic radiation planes of two loudspeakers  
included in an on-vehicle amplification-sound apparatus  
of Embodiment 23 of the present invention is  $1/2$  of the  
wavelength of the reproduced sound.

10

15        Figure 35C a diagram illustrating a boundary  
element method simulation result of a directional  
radiation pattern obtained when the interval between  
the acoustic radiation planes of two loudspeakers  
included in an on-vehicle amplification-sound apparatus  
of Embodiment 23 of the present invention is  $2/3$  of the  
wavelength of the reproduced sound.

20        Figure 35D a diagram illustrating a boundary  
element method simulation result of a directional  
radiation pattern obtained when the interval between  
the acoustic radiation planes of two loudspeakers  
included in an on-vehicle amplification-sound apparatus  
of Embodiment 23 of the present invention is  $8/9$  of the  
25        wavelength of the reproduced sound.

30        Figure 36 is a plan view schematically  
illustrating extension of respective radiated sounds  
from an amplified sound source and a control sound  
source at a control frequency when the interval between  
the amplified sound source and the control sound source  
is  $1/4$  of the wavelength  $\lambda$  for the control frequency.

Figure 37A is a cross-sectional view illustrating the extension of the radiated sound (amplified sound) from the amplified sound source in Figure 36.

5

Figure 37B is a cross-sectional view of the extension of the radiated sound (control sound) from the control sound source in Figure 36.

10

Figure 37C is a cross-section view illustrating the obtained waveform from the interference between the amplified sound in Figure 37A and the control sound in Figure 37B.

15

Figure 38 is a plan view is a diagram schematically illustrating extension of respective radiated sounds from an amplified sound source and a control sound source at a control frequency when the interval between the amplified sound source and the control sound source is  $1/2$  of the wavelength  $\lambda$  for the control frequency.

20

Figure 39A is a cross-sectional view illustrating the extension of the radiated sound (amplified sound) from the amplified sound source in Figure 38.

25

Figure 39B is a cross-sectional view illustrating the extension of the radiated sound (control sound) from the control sound source in Figure 38.

30

Figure 39C is a cross-section view illustrating

09436864-060800

the obtained waveform from the interference between the amplified sound in Figure 39A and the control sound in Figure 39B.

5 BEST MODE FOR CARRYING OUT THE INVENTION

Hereinafter, the present invention will be described with reference to the accompanying drawings by way of examples illustrated therein.

10 Embodiment 1

A sound-amplification apparatus according to Embodiment 1 of the present invention will be described with reference to the figures. Figure 5 is a diagram schematically illustrating the structure of a sound-amplification apparatus 100 of the present embodiment.  
15 The sound-amplification apparatus 100 includes an amplified sound source 1, a control sound source 2, an acoustic signal source 3 and signal processing means 4.

20 The amplified sound source 1 converts an acoustic signal from the acoustic signal source 3 to an amplified sound and radiates the amplified sound. On the other hand, the control sound source 2 converts a control sound signal from the signal processing means 4  
25 to a control sound and radiates the control sound. The amplified sound source 1 and the control sound source 2 are provided in the opposite directions with respect to each other. The sound sources 1 and 2 do not have to be arranged along the same axis as illustrated in the  
30 figure. The signal processing means 4 produces a control sound signal by performing a signal processing operation on the acoustic signal from the acoustic signal source 3 with respect to the amplitude or the

008090" 49898460

phase thereof.

With the sound-amplification apparatus 100 having such a structure, interference occurs between the amplified sound from the amplified sound source 1 and the control sound from the control sound source 2. Therefore, it is possible to change the directional radiation pattern of the amplified sound source 1 by the control sound from the control sound source 2. Thus, it is possible to realize various directional radiation patterns based on the characteristic setting of the signal processing means 4 without requiring a change in the structure of the loudspeaker system which is the amplified sound source 1.

#### Embodiment 2

Next, a sound-amplification apparatus according to Embodiment 2 of the present invention will be described with reference to the figures.

Figure 6 is a diagram illustrating an internal structure of the signal processing means 4 which is used in the sound-amplification apparatus of the present embodiment. The other elements of the present embodiment are substantially the same as those of the sound-amplification apparatus 100 illustrated in Figure 5, and thus will not be further described. Figures 7A to 7E are waveform diagrams illustrating exemplary signals related to the amplified sound source and the control sound source.

As illustrated in Figure 6, the signal processing means 4 includes an error detector 5,

(1) a control sound signal S3 (see Figure 7C) having substantially the same amplitude and inverted phase from those of the signal S2;

(2) a control sound signal S4 (see Figure 7D) having substantially the same amplitude and inverted

phase characteristic from those of the acoustic signal source S1; and

(3) a control sound signal S5 (see Figure 7E) having substantially the same amplitude and same phase characteristic as those of the acoustic signal source S1.

Where the calculation means 6 outputs the control sound signal S3, the amplified sound at the position of the error detector 5 is canceled by a control sound output from the control sound source 2. Therefore, the amplified sound has a unidirectional radiation pattern with the least sound pressure being radiated toward the error detector 5.

Where the calculation means 6 outputs the control sound signal S4, the control sound radiated from the control sound source 2 and the amplified sound radiated from the amplified sound source 1 have substantially the same amplitude and inverted phases from each other. Therefore, the amplified sound in this case is bidirectional where the acoustic radiation has its main axes directed forwardly from the amplified sound source 1 and the control sound source 2, respectively, with the least sound pressure occurring in a direction perpendicular to the main axes of the acoustic radiation. Thus, a dipole directional radiation pattern is realized.

Where the calculation means 6 outputs the control sound signal S5, the control sound radiated from the control sound source 2 and the amplified sound radiated from the amplified sound source 1 have

008090"49898460

substantially the same amplitude and same phase as each other. The acoustic radiation in this case is such that the amplified sound is omni-directionally and uniformly radiated about the center of gravity between the amplified sound source 1 and the control sound source 2 which are considered as a pair of sound sources. Thus, a non-directional radiation pattern is realized.

As described above, the control sound signal which is output from the calculation means 6 to the control sound source 2 is changed based on the output from the directional radiation pattern selection means 7, thereby changing the directional radiation pattern of the amplified sound. The selection among the directional radiation patterns is performed by the directional radiation pattern selection means 7. Thus, it is possible to realize various directional radiation patterns without requiring a change in the structure of the loudspeaker system.

In the present embodiment, the calculation means 6 is illustrated to function: to produce the control sound signal S3 having an amplitude and a phase characteristic for controlling the output signal S2 from the error detector 5 to be 0; to produce the control sound signal S4 having substantially the same amplitude and inverted phase characteristic from those of the output S1 from the acoustic signal source 3; or to produce the control sound signal S5 having substantially the same amplitude and same phase characteristic as those of the output S1 from the acoustic signal source 3. However, the calculation means 6 may alternatively produce a control sound

signal which provides any amplitude and/or phase other than those described above based on the output from the directional radiation pattern selection means 7, thereby realizing any other directional radiation pattern.

### Embodiment 3

Next, a sound-amplification apparatus according to Embodiment 3 of the present invention will be described with reference to the figures.

Figure 8 is a diagram illustrating the positional relationship between the amplified sound source 1 and the control sound source 2 used in the sound-amplification apparatus of the present embodiment. The other elements of the present embodiment are substantially the same as those of the sound-amplification apparatus 100 illustrated in Figure 5, and thus will not be further described.

In the sound-amplification apparatus of the present embodiment, the amplified sound source 1 and the control sound source 2 are provided along the same axis in the opposite directions with respect to each other so that an acoustic radiation plane 1a of the amplified sound source 1 and an acoustic radiation plane 2a of the control sound source 2 are symmetrically arranged. With such an arrangement, the acoustic space will be axially symmetric with respect to a straight line L which passes through the center of the acoustic radiation plane 1a and the center of the acoustic radiation plane 2a. Therefore, the directional radiation pattern which results from the interference



between the amplified sound from the amplified sound source 1 and the control sound from the control sound source 2 will also be axially symmetric with respect to the straight line L. This facilitates the positioning of the sound-amplification apparatus.

#### Embodiment 4

A sound-amplification apparatus according to Embodiment 4 of the present invention will be described with reference to the figures.

Figure 9 is a diagram illustrating the positional relationship among the amplified sound source 1, the control sound source 2 and the error detector 5 used in the sound-amplification apparatus of the present embodiment. The other elements of the present embodiment are substantially the same as those of the sound-amplification apparatus 100 illustrated in Figure 5, and thus will not be further described.

Figure 10 shows an exemplary directional radiation pattern obtained by the sound-amplification apparatus of the present embodiment.

As illustrated in Figure 9, the error detector 5 is a non-directional microphone which is provided in the vicinity of the control sound source 2 and along the straight line L which passes through the center of the acoustic radiation plane 1a and the center of the acoustic radiation plane 2a. With such an arrangement, the amplified sound source 1, the control sound source 2 and the error detector 5 are aligned along the same straight line L. Therefore, when the amplified

09486864-060800

5 sound from the amplified sound source 1 is interfered with, and canceled out by, the control sound from the control sound source 2 at the position of the error detector 5 (i.e., when the output from the error detector 5 is controlled to be 0), the obtained directional radiation pattern will be axially symmetric with respect to the straight line L. This facilitates the positioning of the sound-amplification apparatus.

10 A directional radiation pattern which is obtained when the output from the error detector 5 is controlled to be 0 has been described above in the present embodiment. However, it is possible to obtain through a similar signal processing operation any other  
15 directional radiation pattern by controlling the output from the error detector 5 to be any value other than 0. It is understood that the acoustic space resulting in such a case will also be axially symmetric with respect to the straight line L which passes through the center  
20 of the acoustic radiation plane 1a and the center of the acoustic radiation plane 2a.

25 In the present embodiment, a non-directional microphone is used as the error detector 5. However, it is understood that substantially the same effects can be obtained even with any other detector, e.g., a directional microphone or a vibrometer, capable of detecting the amplified sound at the position where the error detector 5 is provided.

30

#### Embodiment 5

A sound-amplification apparatus according to Embodiment 5 of the present invention will be described

Figure 11 is a diagram schematically illustrating the sound-amplification apparatus of the present embodiment, and more particularly the calculation means 6, other elements in the vicinity of the calculation means 6, and the flow of a control signal therethrough. The other elements may be substantially the same as those of any of the sound-amplification apparatuses illustrated in the foregoing embodiments, and thus will not be further described.

When an output from the error detector 5 is input to the directional radiation pattern selection means 7, the directional radiation pattern selection means 7 outputs to the coefficient updatator 10 an output signal (an error signal) whose amplitude and phase characteristics have been adjusted based on a signal from the error detector 5 and an acoustic signal from the acoustic signal source 3. On the other hand, the output from the acoustic signal source 3 is input to the adaptive filter 8 and the FX filter 9. The output from the FX filter 9 is input to the coefficient updatator 10 as a reference signal. The coefficient updatator 10 uses an LMS (Least Mean Square) algorithm,

or the like, to update the coefficient of the adaptive filter 8 by performing a coefficient update calculation such that the error signal is always small. The output signal from the adaptive filter 8 is provided to the control sound source 2.

Assuming that the transfer function from the amplified sound source 1 to the error detector 5 is G and the transfer function from the control sound source 2 to the error detector 5 is C, then, the characteristic of the FX filter 9 is set to C. When the coefficient updatator 10 is operated to cause the adaptive filter 8 to converge while setting the output signal from the directional radiation pattern selection means 7 to be equal to the output signal from the error detector 5, the output signal from the directional radiation pattern selection means 7 approaches 0, and the adaptive filter 8 converges to a characteristic of  $-G/C$ . Thus, for an acoustic signal  $s$ , a radiated sound from the amplified sound source 1 as it is received at the error detector 5 (an amplified sound) is represented as:

$$s \cdot G.$$

On the other hand, the control sound from the control sound source 2 as it is received at the error detector 5 is represented as:

$$s \cdot (-G/C) \cdot C = -s \cdot G.$$

The amplified sound and the control sound interfere with each other at the position of the error detector 5. Thus,

$$s \cdot G + (-s \cdot G) = 0.$$

008090"49898460

5

10

15

20

25

30

Therefore, the amplified sound and the control sound will have the same amplitude and same phase as each

other. In such a case, due to the interference therebetween, a non-directional radiation pattern is obtained.

5           The present embodiment illustrates three  
different cases, where the directional radiation  
pattern selection means 7 respectively outputs: a  
signal having substantially the same amplitude and same  
phase characteristic as those of the error detector 5;  
10 a signal having a characteristic which is obtained by  
convoluting a signal having substantially the same  
amplitude and same phase characteristic as those of the  
output from the acoustic signal source 3 with a  
transfer function from the control sound source 2 to  
15 the error detector 5; and a signal having a  
characteristic which is obtained by convoluting a  
signal having substantially the same amplitude and  
inverted phase characteristic from those of the output  
from the acoustic signal source 3 with a transfer  
20 function from the control sound source 2 to the error  
detector 5. Other than these cases, the directional  
radiation pattern selection means 7 can alternatively  
switch among different directional radiation patterns  
so as to control the amplitude and/or the phase of the  
25 output signal to an intended value.

On the other hand, the control signal output  
from the adaptive filter 8 to the control sound  
source 2 is changed according to the output from the  
30 directional radiation pattern selection means 7. Thus,  
the present sound-amplification apparatus can form any  
directional radiation pattern other than those  
described above.

09486864-060800

## Embodiment 6

Next, a sound-amplification apparatus according to Embodiment 6 of the present invention will be described with reference to the figures.

In the sound-amplification apparatus of the present embodiment, a horn loudspeaker system as illustrated in Figure 12 is employed as the loudspeaker system for one or both of the amplified sound source 1 and the control sound source 2. The other elements may be substantially the same as those of any of the sound-amplification apparatuses illustrated in the foregoing embodiments, and thus will not be further described.

Referring to Figure 12, the horn loudspeaker system includes a horn driver 11 and an acoustic tube 12. The acoustic tube 12 has a continuously varied cross-sectional area along a plane perpendicular to the sound wave traveling direction (the direction indicated by an arrow in the figure). Therefore, the frequency change in the acoustic impedance of the acoustic tube 12 along the axis thereof is reduced, thereby preventing the disturbance in the frequency characteristic of the acoustic radiation from the acoustic tube 12. Thus, it is possible to obtain a desirable directional radiation pattern and a desirable acoustic characteristic.

## Embodiment 7

Next, a sound-amplification apparatus according to Embodiment 7 of the present invention will be described with reference to the figures.

09486864-060800

5 In the sound-amplification apparatus of the present embodiment, the horn loudspeaker system employed for one or both of the amplified sound source 1 and the control sound source 2 has a reentrant horn as illustrated in Figure 13. The other elements may be substantially the same as those of any of the sound-amplification apparatuses illustrated in the foregoing embodiments, and thus will not be further described.

10

15 The horn loudspeaker system includes a horn driver 11 and a reentrant horn 13. Herein,  $d$  is the central axis of the reentrant horn 13, and  $e$  is the horn length of the reentrant horn 13. A sound is radiated from the horn driver 11 to the outside, with its directional radiation pattern being controlled while it is guided through the reentrant horn 13 in the direction indicated by the arrow along the horn central axis  $d$ .

20

25 With such a structure, it is possible to smoothly vary the cross-sectional area along a direction perpendicular to the sound wave traveling direction through the reentrant horn 13 without having to increase the horn length  $e$ . Therefore, the frequency change in the acoustic impedance of the reentrant horn 13 is reduced, whereby the acoustic radiation from the reentrant horn 13 has a reduced disturbance in its sound pressure frequency characteristic. Thus, a desirable directional radiation pattern and a desirable acoustic characteristic can be obtained even with a reduced size. Moreover, by folding back the horn, it is

30



possible to prevent wind and rain from entering the horn driver 11.

5        Figure 13 illustrates a case where the horn is folded back twice. However, it is understood that substantially the same effects can be obtained with any other number of times the horn is folded back.

10       For example, the horn loudspeaker system shown in Figure 14 includes a reentrant horn 14 which is folded back three times, and a horn driver 11. The reentrant horn 14 has acoustic radiation plane 14a of its open end, and the plane is in a direction opposite to the output direction of the horn driver 11. A sound  
15       is radiated from the horn driver 11 to the outside, with its directional radiation pattern being controlled while it is guided through the reentrant horn 14 in the direction indicated by the arrow along the horn central axis d.

20       With such a structure, it is possible to smoothly vary the cross-sectional area along a direction perpendicular to the sound wave traveling direction through the reentrant horn 14 without having  
25       to increase the horn length e. Therefore, the reentrant horn 14 also has a reduced frequency change in the acoustic impedance, whereby the acoustic radiation from the reentrant horn 14 has a reduced disturbance in its sound pressure frequency characteristic. Thus, a  
30       desirable directional radiation pattern and a desirable acoustic characteristic can be obtained even with a reduced size.

09486864-060800

Furthermore, as illustrated in Figure 15, because the horn is folded back an odd number of times, when employing a reentrant horn of this structure for each of an amplified sound source 1 and a control sound source 2, the length  $f$  between acoustic radiation planes 1a and 2a, which are open ends of the reentrant horns, can be reduced. Thus, a dipole directional radiation pattern of a narrow directionality angle can be obtained. Moreover, by folding back the horn, it is possible to prevent wind and rain from entering the horn driver 11.

Figures 14 and 15 illustrate a case where the horn is folded back three times. However, it is understood that substantially the same effects can be obtained with any other odd number of times the horn is folded back.

Figure 13 illustrates a case where the horn is folded back twice. However, it is understood that substantially the same effects can be obtained with any other number of times the horn is folded back.

As described above, with the amplified sound apparatuses according to Embodiments 1 through 7 of the present invention, a control sound source is provided in the vicinity of an amplified sound source, whereby a predetermined directional radiation pattern can be realized. Moreover, when each of an amplified sound source and a control sound source is a horn loudspeaker including a horn driver and an acoustic tube, better directional and acoustic characteristics are achieved for an externally radiated sound. When a reentrant horn

is used as an acoustic tube, a sound-amplification apparatus with a reduced size is realized.

#### Embodiment 8

5           A directional loudspeaker apparatus 210 as a sound-amplification apparatus according to Embodiment 8 of the present invention will be described with reference to the figures.

10           Figure 16 is a diagram schematically illustrating a structure of the directional loudspeaker apparatus 210 of the present embodiment. The directional loudspeaker apparatus 210 includes a reflector 201 and a sound source 202A. The sound  
15           source 202A is a loudspeaker which has a directional radiation pattern shown by a curved line a. The sound source 202A has a sound characteristic which is particularly weak in a rearward direction, and a sound receiving point c is in that direction. The sound  
20           source 202A is provided within the reflector 201 so that a sound radiated from the sound source 202A (amplified sound) is mostly reflected by the reflector 201 to reach the sound receiving point c via the route shown by a straight line b.

25           A portion of the sound source 202A which is not covered with the reflector 201 has reduced acoustic radiation, thereby reducing the amount of amplified sound which is directly scattered without being  
30           reflected by the reflector 201. Thus, portions of the amplified sound which reach the sound receiving point c will be in phase with one another, and a sound pressure is added to the amplified sound, whereby a sharp

09485854-060800

directional radiation pattern is achieved.

Each of Figures 17A and 17B shows a sound pressure distribution of an amplified sound radiated by a directional loudspeaker apparatus as obtained by a simulation based on a boundary element method. Figure 17A shows the sound pressure distribution for a conventional directional loudspeaker apparatus, while Figure 17B shows a distribution of the directional loudspeaker apparatus 210 of the present embodiment. Each of Figures 17A and 17B shows a sound pressure level at each point according to the gauge shown in Figure 17C, with the sound pressure level at the sound receiving point c being 0 dB. Accordingly, it can be seen that the sound extension of the directional loudspeaker apparatus 210 of the present embodiment is narrower than that of the conventional directional loudspeaker apparatus in Figure 17A indicating that the directional radiation pattern is controlled sufficiently.

#### Embodiment 9

Next, a directional loudspeaker apparatus 220 as a sound-amplification apparatus according to Embodiment 9 of the present invention will be described with reference to the figures.

Figure 18 is a diagram schematically illustrating a structure of the directional loudspeaker apparatus 220 of the present embodiment. The same elements as those in the directional loudspeaker apparatus 210 of Embodiment 8 are indicated by the same references, and thus will not be further described.

The directional loudspeaker apparatus 220 includes a reflector 201, a sound source 202B, an acoustic signal source 205, and signal processing means 206. As shown in Figure 18, the sound source 202B is provided within the reflector 201. The sound source 202B includes an amplified sound source 203 and a control sound source 204. The amplified sound source 203 is a loudspeaker which converts the acoustic signal from the acoustic signal source 205 to an amplified sound to radiate the amplified sound and is provided facing the center of the reflector 201. The signal processing means 206 controls the amplitude and the phase of the acoustic signals from the acoustic signal source 205 so that the output characteristic of the sound source 202B is unidirectional, thereby outputting the control signal to the control sound source 204 as a control sound signal. The control sound source 204 is a loudspeaker which converts the control sound signal from the signal processing means 206 to a control sound to radiate the control sound and is provided coaxially with, and opposite to, the amplified sound source 203.

25           With such a structure, interference occurs  
between the amplified sound radiated from the amplified  
sound source 203 and the control sound radiated from  
the control sound source 204, and thus the sound  
pressure in the acoustic space directly formed in the  
30   rearward space behind the sound source 202B (in front  
of the control sound source 204) can be further reduced  
by controlling the phase and/or amplitude of the  
control sound source. Therefore, it is possible to

obtain the strong directional radiation pattern as indicated by a curved line a.

5 Since the reflector 201 functions as in Embodiment 8 in connection with the sound source 202B having such a strong directionality, an amplified sound which is radiated from the sound source 202B and reflected by the reflector 201 is more localized at the sound receiving point. Because a direct sound which has  
10 not been reflected by the reflector 201 does not reach the sound receiving point, the sound wave at the sound receiving point has a reduced phase-mismatch, thereby improving the sound pressure at the sound receiving point.

15

Embodiment 10

Next, a directional loudspeaker apparatus 230 as a sound-amplification apparatus according to Embodiment 10 of the present invention will be  
20 described with reference to the figures.

Figure 19 is a diagram schematically illustrating a structure of the directional loudspeaker apparatus 230 of the present embodiment. The same  
25 elements as those in the directional loudspeaker apparatus 220 of Embodiment 9 are indicated by the same references, and thus will not be further described.

The directional loudspeaker apparatus 230  
30 includes a reflector 201, a sound source 202C, an acoustic signal source 205, and signal processing means 206. As in the case of Figure 18, the sound source 202C includes the amplified sound source 203 and

000090"4989460

the control sound source 204 which is provided coaxially with, and opposite to, each other.

5       The signal processing means 206 includes an  
error detector 207, an adaptive filter 208, a filtered  
X-filter (an FX filter) 209, and a coefficient  
updater 210. The error detector 207 is a microphone  
which is provided in the vicinity of the control sound  
source 204. The FX filter 209 is a filter which is set  
10   to a characteristic equal to a transfer function C from  
the control sound source 204 to the error detector 207.  
The adaptive filter 208 is a filter which performs a  
convolution calculation on the acoustic signal input  
from the acoustic signal source 205 with a transfer  
15   function F, and provides the obtained calculation  
result to the control sound source 204 as a control  
sound signal.

20       The coefficient updater 210 uses an LMS (Least  
Mean Square) algorithm, or the like, with the output  
from the FX filter 209 being a reference signal and the  
output from the error detector 207 being an error  
signal, to update the coefficient of the adaptive  
filter 208 by performing a coefficient update  
25   calculation such that the error signal is minimized.

30       It is assumed that the transfer function from  
the amplified sound source 203 to the error  
detector 207 is G and the transfer function from the  
control sound source 204 to the error detector 207 is C.  
When the coefficient updater 210 is operated to cause  
the adaptive filter 208 to converge, the output signal  
from the error detector 207 approaches 0. In this case,

09486864-060800

the transfer function  $F$  of the adaptive filter 208 converges to a characteristic of  $-G/C$ .

5 For an acoustic signal  $s$ , a radiated sound from the amplified sound source 203 as it is received at the error detector 207 is represented as:

$$s \cdot G.$$

10 On the other hand, the control sound from the control sound source 204 as it is received at the error detector 207 is represented as:

$$s \cdot (-G/C) \cdot C = -s \cdot G.$$

15 Therefore, the amplified sound and the control sound interfere with each other at the position of the error detector 207. Thus,

$$s \cdot G + (-s \cdot G) = 0.$$

20 In this manner, at the position of the error detector 207, the amplified sound is canceled out by the control sound, thereby realizing a directional radiation pattern with the least acoustic radiation toward the position of the error detector 207. As a result, a direct sound which has not been reflected by  
25 the reflector 201 does not reach the sound receiving point. Therefore, an amplified sound with a high sound pressure is localized at the sound receiving point, whereby the directional radiation pattern becomes sharper.

30

Embodiment 11

Next, a directional loudspeaker apparatus 240 as a sound-amplification apparatus according to

09485854-060800



Embodiment 11 of the present invention will be described with reference to the figures.

Figure 20 is a diagram schematically illustrating a structure of the directional loudspeaker apparatus 240 of the present embodiment. The same elements as those in the directional loudspeaker apparatus 230 of Embodiment 10 are indicated by the same references, and thus will not be further described.

10                   The directional loudspeaker apparatus 240  
includes a reflector 201, a sound source 202D, an  
acoustic signal source 205, and signal processing  
means 206. The sound source 202D includes the amplified  
15 sound source 203 and the control sound source 204  
provided coaxially with, and opposite to each other as  
in the case of Figure 19. The signal processing  
means 206 includes an error detector 207, an adaptive  
filter 208, an FX filter 209, and a coefficient  
20 updatator 210, as in Embodiment 10.

In the directional loudspeaker apparatus 240, a signal correction means 211 is provided between the acoustic signal source 205 and the amplified sound source 203. Assuming that the time required by the signal processing means 206 for a signal processing operation is  $\tau_1$ , and the time required for the control sound radiated from the control sound source 204 to reach the error detector 207 is  $\tau_2$ , the signal correction means 211 sets a delay time which is approximately equal to  $\tau_1 + \tau_2$  for the acoustic signal  $s$ , and desirably controls the amplitude and the phase of the acoustic signal  $s$ . The signal correction means 211

outputs the obtained signal as a result of such a process to the amplified sound source 203.

With such an arrangement, it is possible to adjust the delay time of the signal which is input to the amplified sound source 203 with the signal correction means 211. Thus, a desirable directional radiation pattern can be realized even when the distance from the amplified sound source 203 to the error detector 207 is shorter than that from the control sound source 204 to the error detector 207, and when an amount of time is required for signal processing by the FX filter 209, the coefficient updater 210, and the adaptive filter 208. For example, when the amount of time required for processing by the signal processing means 206 is longer than the propagation time of the amplified sound, the causality between the above-mentioned transfer functions is not satisfied. However, the directional loudspeaker apparatus 240 avoids such a problem. Moreover, the signal correction means 211 can desirably correct the acoustic characteristic such as the amplitude and the phase of the amplified sound radiated from the amplified sound source 203, whereby a listener can receive a sound with a desirable sound quality.

## Embodiment 12

Next, a directional loudspeaker apparatus as a sound-amplification apparatus according to Embodiment 12 of the present invention will be described with reference to the figures.

Figure 21 only illustrates a sound source 202E

among other elements of the directional loudspeaker apparatus of the present embodiment. In the sound source 202E, the amplified sound source 203 and the control sound source 204 are provided coaxially with each other. Specifically, the control sound source 204 is coaxially arranged so that an acoustic radiation plane 204a is symmetrical with an amplified sound plane 203a of the amplified sound source 203. An error detector 207 is provided in front of the control sound source 204. The other elements may be the same as those of any of the sound-amplification apparatuses illustrated in the foregoing embodiments.

With such an arrangement, a directional radiation pattern obtained by interference between the amplified sound from the amplified sound source 203 and the control sound from the control sound source 204 can be axially symmetrical, the sound pressure directional radiation pattern can also be unidirectional, thereby facilitating the positioning of the sound source 202E.

#### Embodiment 13

Next, a directional loudspeaker apparatus 260 as a sound-amplification apparatus according to Embodiment 13 of the present invention will be described with reference to the figures.

Figure 22 only illustrates a sound source 202F among other elements of the directional loudspeaker apparatus 260 of the present embodiment. In the sound source 202F, the positions of an amplified sound source 203, a control sound source 204, and an error detector 207 are provided coaxially with one another.

Moreover, the error detector 207 is arranged in the vicinity of the control sound source 203 and along a straight line L which passes through the center of an acoustic radiation plane 203a and the center of an acoustic radiation plane 204a. The other elements may be the same as those of any of the sound-amplification apparatuses illustrated in the foregoing embodiments.

With such an arrangement, when the amplified sound from the amplified sound source 203 interferes with, and is canceled out by, the control sound from the control sound source 204 at the position of the error detector 207, the resulting directional radiation pattern a will be axially symmetric with respect to the straight line L, thereby facilitating the positioning of the sound source 202F.

As described above, according to the directional loudspeaker apparatuses of Embodiments 8 through 13 of the present invention, an amplified sound radiated from the back of the sound source is reduced, and a sharp directional radiation pattern can be realized with a reflector.

In Embodiments 14 through 23 of the present invention to be described below, several embodiments of an on-vehicle sound-amplification apparatus using a sound-amplification apparatus having an intended directionality according to the present invention as an on-vehicle sound-amplification apparatus will be described, as a specific application of the present invention.

## Embodiment 14

Each of Figures 23 and 24 is a diagram illustrating a structure of an amplification-sound apparatus 310 according to Embodiment 14 of the present invention. Specifically, Figure 23 is a diagram schematically illustrating a structure of the apparatus 310 where the amplification-sound apparatus of the present invention is mounted on a truck-type vehicle as an on-vehicle acoustic reproducing apparatus, and Figure 24 is a diagram schematically illustrating a flow of electric signals in such a case. In Figures 23 and 24, reference numeral 301 is a vehicle body, 302 is a dipole sound source, 303 is signal processing means, 304 is a driver, a and a' are main axes of acoustic radiation of the dipole sound source 302, b and b' are directional radiation patterns of the dipole sound source 302, and s is an acoustic signal.

The dipole sound source 302 is provided in the vicinity of the driver 304, the acoustic signal s is amplified by the signal processing means 303 and then input to the dipole sound source 302 to be acoustically radiated therefrom as a reproduced sound. The main axes of the acoustic radiation a and a' form the directional radiation patterns b and b' which are directed to a direction away from the vehicle body 301. On the other hand, in a vicinity of the line between the dipole sound source 302 and the driver 304, the radiated sounds interfere with, and are canceled by, one another. Thus, the radiated sound decreases, whereby substantially no direct sound from the dipole sound source 302 reaches to a location in the vicinity of the driver 304. Therefore, it is possible to obtain a

09486364-060300

desirable sound environment in which a sufficient volume of sound is ensured along the main axes of the acoustic radiation  $a$  and  $a'$ , while reducing the volume of sound in the vicinity of the driver 304.

5

Although the dipole sound source 302 is provided in the vicinity of the driver 304 in Figure 23, when it is provided in the vicinity of any other passenger (e.g., in the vicinity of the passenger seat),  
10 substantially the same effects can be obtained in the vicinity of the respective passenger.

In Figure 23, the present invention is applied to a truck-type vehicle, but substantially the same effects can be obtained with any other type of vehicle,  
15 such as a sedan, a van, or a wagon type, or with any other transportation means such as a ship.

#### Embodiment 15

20 Next, an amplification-sound apparatus 320 according to Embodiment 15 of the present invention will be described with reference to Figures 25 and 26.

Figure 25 is a diagram schematically  
25 illustrating a structure of the apparatus 320 where the amplification-sound apparatus of the present invention is mounted on a truck-type vehicle as an on-vehicle acoustic reproducing apparatus, and Figure 26 is a diagram schematically illustrating a flow of electric  
30 signals in such a case. The same elements as those of Embodiment 15 are indicated by the same references, and thus will not be further described. This also applies to each of the subsequent embodiments.

000000"4989460

09485864-060800

5 In Figure 25 and 26, reference numeral 305 is a non-directional sound source, c is a directional radiation pattern of the non-directional sound source 305, d is a unidirectional radiation pattern which is achieved in the present embodiment.

10 A dipole sound source 302 is provided in the vicinity of the driver 304, the non-directional sound source 305 is provided in the central portion of the dipole sound source 302. An acoustic signal s is amplified and phase-adjusted by the signal processing means 303, and the acoustic signal s is then input to the dipole sound source 302 and the non-directional sound source 305 to be acoustically radiated therefrom as a reproduced sound.

20 An acoustic radiation main axis a' of the dipole sound source 302 is directed toward the driver 304 and forms a directional radiation pattern b'. On the other hand, an acoustic signal s is amplified and phase-adjusted by the signal processing means 303 so as to have a phase substantially opposite to that of the acoustic radiation forming the directional radiation pattern b', and the signal is input to the non-directional sound source 305. The non-directional sound source 305 acoustically radiates signal as a reproduced sound simultaneously with the dipole sound source 302.

30 With such an arrangement, a sound radiated from the dipole sound source 302 and a sound radiated from the non-directional sound source 305 are interfered with, and canceled out by, each other in the vicinity

of the driver 304. Thus, the radiated sound decreases, and the directional radiation pattern d becomes a unidirectional radiation pattern directed exclusively along the acoustic radiation main axis a. Therefore, it is possible to obtain a desirable sound environment in which a sufficient volume of sound is ensured along the acoustic radiation main axis a, while the volume of sound is reduced in the vicinity of the driver 304.

In the present embodiment, when the dipole sound source 302 is provided in the vicinity of any other passenger (e.g., in the vicinity of the passenger seat), substantially the same effects can be obtained in the vicinity of the respective passenger. With any other types of vehicles such as a sedan, a van, or a wagon type, or with any other transportation means such as a ship, substantially the same effects can also be obtained.

#### Embodiment 16

Figure 27 is a diagram illustrating a flow of electric signals in an amplification-sound apparatus 330 according to Embodiment 16 of the present invention. Figures 28A to 28D are diagrams respectively illustrating various directional radiation patterns e1 to e4 of acoustic radiation obtained by the amplification-sound apparatus 330 of the present embodiment.

In Figure 27, reference numerals 306 and 307 are loudspeakers arranged so that the respective acoustic radiation planes thereof are directed opposite to each other. Reference numeral e1 in Figure 28A is a



directional radiation pattern of an acoustic radiation which is obtained when the phase difference between the loudspeaker 306 and the loudspeaker 307 is  $180^\circ$ , e2 in Figure 28B is a directional radiation pattern of the acoustic radiation which is obtained when the aforementioned phase difference is  $150^\circ$ . Similarly, e3 shown in Figure 28C and e4 shown in Figure 28D are directional radiation patterns of the acoustic radiation which are obtained when the aforementioned phase difference are  $120^\circ$  and  $90^\circ$ , respectively.

In the present embodiment, the phase difference between the radiated sounds respectively from the loudspeakers 306 and 307 can be varied since the phase of an acoustic signal input to at least one of the loudspeakers can be varied by the signal processing means 303. Thus, the positions in which the reproduced sounds from the loudspeakers 306 and 307 are interfered with, and canceled out by each other, can be changed to directional radiation patterns e1 to e4. Thus, even when the loudspeaker is not provided in the vicinity of the driver 304, substantially the same effects can be obtained as those obtained when the loudspeaker is provided in the vicinity of the driver 304.

#### Embodiment 17

Figure 29 is a diagram schematically illustrating a structure of an amplification-sound apparatus 340 according to Embodiment 17 of the present invention.

In Figure 29, reference numerals 308 and 309 are acoustic tubes provided in loudspeakers 306 and 307,

respectively. Each of the acoustic tubes 308 and 309 has a continuously varied cross-sectional area along a plane perpendicular to the sound wave traveling direction. Therefore, the frequency change in the acoustic impedance of the acoustic tubes 308 and 309 along the axes thereof is reduced, thereby reducing the disturbance in the sound pressure frequency characteristic of the radiated sound from the acoustic tubes 308 and 309. Thus, it is possible to obtain a desirable directional radiation pattern and a desirable acoustic characteristic.

In the present embodiment, acoustic tubes are used for the loudspeakers 306 and 307, but it is understood that when using horn drivers for the loudspeakers 306 and 307 instead of the tubes, substantially the same effects can be obtained. This also applies to each of the subsequent embodiments.

#### Embodiment 18

Next, a sound-amplification apparatus 350 according to Embodiment 18 of the present invention will be described with reference to Figure 30.

In Figure 30, reference numeral 310 is a radiated sound detector, 311 is an error detector, 312 is an adder, and 313 is calculation means. The radiated sound from a loudspeaker 306 to which the acoustic signal *s* is directly input is detected at the radiated sound detector 310, and the obtained result is input to the adder 312. The control sound from a loudspeaker 307 is detected at the error detector 311, and the obtained result is also input to the adder 312. After adding the

two above-described inputs in the adder 312, the output therefrom is input to the calculation means 313. The calculation means 313, to which the acoustic signal  $s$  and the output from the adder 312 are input, uses an LMS (Least Mean Square) algorithm, or the like, to perform a calculation such that the output from the adder 312 is always small, and then outputs the obtained signal to the loudspeaker 307 as a control signal.

The radiated sound detector 310 and the error detector 311 are provided in the vicinity of the loudspeakers 306 and 307, respectively. With this arrangement, assuming that the transfer function from the loudspeaker 306 to the radiated sound detector 310 is  $G$  and the transfer function from the loudspeaker 307 to the error detector 311 is  $C$ , the calculation means 313 has a characteristic of  $-G/C$  when the calculation means 313 is operated and the output from the adder 312 approaches 0. Thus, for an acoustic signal  $s$ , a radiated sound from the loudspeaker 306 as it is received at the radiated sound detector 310 is represented as:

$$s \cdot G.$$

On the other hand, the control sound from the loudspeaker 307 as it is received at the error detector 311 is represented as:

$$s \cdot (-G/C) \cdot C = -s \cdot G.$$

The output from the radiated sound detector 310 and the output from the error detector 311 as they are added at the adder 312 is represented as:

$$s \cdot G + (-s \cdot G) = 0.$$

Therefore, by arranging the positions of the radiated sound detector 310 and the error detector 311 so that the transfer function from the loudspeaker 306 to the radiated sound detector 310 and the transfer function from the loudspeaker 307 to the error detector 311 are equal to each other, the radiated sound from the loudspeaker 306 and that from the loudspeaker 307 have the same sound pressure and phases that are different from each other by 180°, thus the variation in the characteristics of the loudspeakers in use is corrected and a desirable dipole characteristic can be obtained. Since the above-described effects are suitably provided while the signal processing means 303 is in operation, it is possible to address a non-linear change such as aging of the apparatus.

#### Embodiment 19

Figure 31 is a diagram schematically illustrating a structure of the amplification-sound apparatus 360. In particular, Figure 31 illustrates the structure of the calculation means 313 of the amplification-sound apparatus 350 in greater detail.

In Figure 31, reference numeral 314 is an adaptive filter, 315 is a filtered X filter (FX filter) which is set to a characteristic equal to a transfer function from a loudspeaker 307 to an error detector 311, and 316 is a coefficient updater.

The output from an adder 312 is input to an error input terminal of the coefficient updater 316, an

acoustic signal  $s$  is input to the adaptive filter 314 and the FX filter 315, and the output signal from the FX filter 315 is input to a reference input terminal of the coefficient upator 316. The coefficient upator 316 uses an LMS (Least Mean Square) algorithm, or the like, to perform a coefficient updating calculation such that the error input is always small, thereby updating the coefficient of the adaptive filter 314. The output signal from the adaptive filter 314 is input to the loudspeaker 307.

Assuming that the transfer function from the loudspeaker 306 to the radiated sound detector 310 is  $G$  and the transfer function from the loudspeaker 307 to the error detector 311 is  $C$ , then, the characteristic of the FX filter 315 is  $C$ . When the coefficient upator 316 is operated to cause the adaptive filter 314 to converge, and thus the output signal from the adder 312 approaches 0, the adaptive filter 314 converges to the characteristic of  $-G/C$ . Therefore, for an acoustic signal  $s$ , a radiated sound from the loudspeaker 306 as it is received at the radiated sound detector 310 is represented as:

$$s \cdot G.$$

On the other hand, the control sound from the loudspeaker 307 as it is received at the error detector 311 is represented as:

$$-s \cdot (-G/C) \cdot C = -s \cdot G.$$

Therefore, by arranging the positions of the radiated sound detector 310 and the error detector 311 so that the transfer function from the loudspeaker 306

10

## 15

20

25

30

The signals input to the first adder 319 and the second adder 320 is added, and output the obtained values to the first calculation means 321 and the second calculation means 322, respectively.

5

10 The acoustic signal  $s$  and the output from the first adder 319 are input to the first calculation means 321, while the acoustic signal  $s$  and the output from the second adder 320 are input to the second calculation means 322. By using an LMS (Least Mean Square) algorithm, or the like, the first calculation means 321 performs a calculation such that the output from the first adder 319 is always small, while the second calculation means 322 performs a calculation such that the output from the second adder 320 is always small, and then outputs the obtained signals to the loudspeaker 307 and the non-directional sound source 305 as control signals, respectively. The radiated sound detector 310 and the error detector 317 are provided in the vicinity of the loudspeakers 306 and 307, respectively, while the second error detector 318 is provided in the vicinity of the non-directional sound source 305.

25 With this arrangement, assuming that the transfer function from the loudspeaker 306 to the radiated sound detector 310 is  $G$  and the transfer function from the loudspeaker 307 to the first error detector 317 is  $C$ , the first calculation means 321 converges to a characteristic of  $-G/C$  when the first calculation means 321 is operated and the output from the first adder 319 approaches 0. Thus, for an acoustic signal  $s$ , a radiated sound from the loudspeaker 306 as

09446354-060800

it is received at the radiated sound detector 310 is represented as:

$$s \cdot G.$$

5 On the other hand, the control sound from the loudspeaker 307 as it is received at the first error detector 317 is represented as:

$$s \cdot (-G/C) \cdot C = -s \cdot G.$$

10 Thus, the output from the radiated sound detector 310 and the output from the first error detector 317 as they are added at the first adder 319 is represented as:

$$s \cdot G + (-s \cdot G) = 0.$$

15

As described above, by arranging the positions of the radiated sound detector 310 and the first error detector 317 so that the transfer function from the loudspeaker 306 to the radiated sound detector 310 and the transfer function from the loudspeaker 307 to the first error detector 317 are equal to each other, the radiated sound from the loudspeaker 306 and that from the loudspeaker 307 have the same sound pressure and phases that are different from each other by 180°, thus  
20 the variation in the characteristics of the loudspeakers in use is corrected and a desirable dipole characteristic can be obtained.

25

Further, assuming that the transfer function from the non-directional sound source 305 to the second error detector 318 is D and the transfer function characteristic of the signal correction means 323 is H,  
30 when the second calculation means 322 is operated and



the output from the second adder 320 approaches 0, the second calculation means 322 converges to a characteristic of  $G/(D \cdot H)$ . On the other hand, for an acoustic signal  $s$ , a radiated sound from the loudspeaker 307 as it is received at the first error detector 317 is represented as:

$$-s \cdot G,$$

and the control sound by the non-directional sound source 305 as it is received at the second error detector 318 is represented as:

$$s \cdot (G/(D \cdot H)) \cdot D = s \cdot G/H,$$

and the output signal from the signal correction means 323 is represented as:

$$s \cdot G/H \cdot H = s \cdot G.$$

The output from the first error detector 317 and the output from the signal correction means 323 as they are added at the second adder 320 is represented as:

$$-s \cdot G + s \cdot G = 0.$$

Therefore, by changing the transfer function characteristic  $H$  of the signal correction means 323, it becomes possible to readily correct the acoustic radiation conditions of the non-directional sound source 305. For example, when arranging the transfer function from the loudspeaker 307 to the first error detector 317 and the transfer function from the non-directional sound source 305 to the second error detector 318 to be equal, the phase of the radiated sound of the non-directional sound source 305 is varied by  $180^\circ$  with respect to the radiated sound of the

loudspeaker 307 while the amplitudes thereof are substantially the same, a unidirectional radiation pattern can be obtained. In this case, if the acoustic radiation main axis of the unidirectional radiation pattern is directed opposite to the position of a passenger (e.g., the driver 304), the direct sound from the sound source scarcely reaches the passenger, thereby attaining a desirable sound environment.

10 Embodiment 21

Figure 33 is a diagram illustrating a structure of the amplification-sound apparatus 380 according to Embodiment 21 of the present invention, more specifically, illustrating the structures of the first calculation means 321 and the second calculation means 322 of the amplification-sound apparatus 370 of Embodiment 20 in more detail.

In Figure 33, 324 is a first adaptive filter, 325 is a first FX filter which is set to a characteristic equal to a transfer function from a loudspeaker 307 to a first error detector 317, 326 is a first coefficient upator, 327 is a second adaptive filter, 328 is a second FX filter which is set to a characteristic equal to a transfer function from a non-directional sound source 305 to a second error detector 318, and 329 is a second coefficient upator.

The output from a first adder 319 is input to an error input terminal of the first coefficient upator 326, an acoustic signal  $s$  is input to the first adaptive filter 324 and the first FX filter 325, and the output signal from the first FX filter 325 is input

to a reference input terminal of the first coefficient updatator 326. The first coefficient updatator 326 uses an LMS (Least Mean Square) algorithm, or the like, performing a coefficient updating calculation such that the error input is always small, and updates the coefficient of the first adaptive filter 324. The output signal from the first adaptive filter 324 is output to the loudspeaker 307. Assuming that the transfer function from the loudspeaker 306 to the radiated sound detector 310 is G and the transfer function from the loudspeaker 307 to the first error detector 317 is C, and then the characteristic of the first FX filter 325 is C.

When the first coefficient updatator 326 is operated to cause the first adaptive filter 324 to converge, and thus the output signal from the adder 319 approaches 0, the characteristic of the first adaptive filter 324 converges to the characteristic of  $-G/C$ . Therefore, for an acoustic signal  $s$ , a radiated sound from the loudspeaker 306 as it is received at the radiated sound detector 310 is represented as:

$$s \cdot G.$$

On the other hand, the control sound from the loudspeaker 307 as it is received at the first error detector 317 is represented as:

$$-s \cdot (-G/C) \cdot C = -s \cdot G.$$

Therefore, by arranging the positions of the radiation sound detector 310 and the first error detector 317 so that the transfer function from the loudspeaker 306 to the radiated sound detector 310 and

09485554-060200

the transfer function from the loudspeaker 307 to the first error detector 317 are equal to each other, the radiated sound from the loudspeaker 306 and that from the loudspeaker 307 have the same sound pressure and phases that are different from each other by  $180^\circ$ , thus the variation in the characteristics of the loudspeakers in use is corrected and a desirable dipole characteristic can be obtained.

On the other hand, the output from a second adder 320 is input to an error input terminal of the second coefficient updatator 329, an acoustic signal  $s$  is input to the second adaptive filter 327 and the second FX filter 328, and the output signal from the second FX filter 328 is input to a reference input terminal of the second coefficient updatator 329. The second coefficient updatator 329 uses an LMS (Least Mean Square) algorithm, or the like, performing a coefficient updating calculation such that the error input is always small, and updates the coefficient of the second adaptive filter 327. The output signal from the second adaptive filter 327 is output to the non-directional sound source 305.

Assuming that the transfer function from the non-directional sound source 305 to the second error detector 318 is  $D$  and the transfer function characteristic of the signal correction means 323 is  $H$ , the characteristic of the second FX filter 328 is  $D \cdot H$ . When the second coefficient updatator 329 is operated to cause the second adaptive filter 327 to converge, and thus the output from the second adder 320 approaches 0, the characteristic of the second adaptive filter 327

converges to a characteristic of  $G/(D \cdot H)$ .

For an acoustic signal  $s$ , a radiated sound from the loudspeaker 307 as it is received at the first error detector 317 is represented as:

$$-s \cdot G.$$

On the other hand, the control sound by the non-directional sound source 305 as it is received at the second error detector 318 is represented as:

$$s \cdot (G/(D \cdot H)) \cdot D = s \cdot G/H,$$

and the output signal from the signal correction means 323 is represented as:

$$s \cdot G/H \cdot H = s \cdot G.$$

Therefore, the output from the first error detector 317 and the output from the signal correction means 323 as they are added at the second adder 320 is represented as:

$$-s \cdot G + s \cdot G = 0.$$

Thus, a unidirectional radiation pattern can be obtained by controlling the transfer function from the loudspeaker 307 to the first error detector 317 to be equal to the transfer function from the non-directional sound source 305 to the second error detector 318, and by changing the phase of the radiated sound of the non-directional sound source 305 by  $180^\circ$  with respect to that of the radiated sound of the loudspeaker 307 with the amplitudes thereof being substantially the same as each other. In this case, if the acoustic radiation main axis of the unidirectional radiation pattern is

directed away from the position of a passenger (e.g., the driver 304), substantially no sound from the sound source reaches directly to the passenger, thereby obtaining a desirable sound environment. Furthermore, with the above-described structure, it is possible to obtain a unidirectional radiation pattern sound source which is not influenced by a change in the operational characteristics due to aging.

10 Embodiment 22

Next, Embodiment 22 of the present invention will be described with reference to Figures 34A and 34B.

Figure 34A is a vertical cross-sectional view of acoustic tubes 308 and 309, and Figure 34B is a horizontal cross-sectional view thereof. In Figure 34A and 34B, reference numeral 330 is a diaphragm of a loudspeaker 306, 331 is a diaphragm of a loudspeaker 307, 332 is an acoustic radiation plane of the acoustic tube 308, 333 is an acoustic radiation plane of the acoustic tube 309, f is a central axis of the acoustic tube 308, f' is a central axis of the acoustic tube 309, and g is a total length of each of the acoustic tubes 308 and 309.

Each of the acoustic tubes 308 and 309 is formed of a curved sound path extending from the diaphragm 330 or 331 to the acoustic radiation plane 332 or 333, respectively. Because the acoustic tubes 308 and 309 are curved, the total length of their central axes f and f' can be long enough even if the total length g of the acoustic tubes is short. Therefore, it is possible to smoothly vary the cross-sectional area along a

direction perpendicular to the sound wave traveling direction through the acoustic tubes 308 and 309 from the diaphragms 330 and 331 through the acoustic radiation planes 332 and 333, respectively. Thus, the frequency change in the acoustic impedance is reduced, thereby attaining a desirable sound pressure frequency characteristic.

Furthermore, when the acoustic tubes 308 and 309 are curved in the vertical and lateral directions, it is possible to provide the acoustic tubes 323 and 333 in a back-to-back arrangement with most of the acoustic tubes 308 and 309 overlapping each other, thereby reducing the size of the apparatus.

#### Embodiment 23

Embodiment 23 of the present invention will be described with reference to Figure 35A through 35D.

Particularly, Figure 35A through 35D illustrate various directional radiation patterns as obtained by a boundary element method when the interval between the acoustic radiation planes 332 and 333 as shown in Figure 34A and 34B, respectively, is varied to  $1/4$ ,  $1/2$ ,  $2/3$ , and  $8/9$  of the wavelength of the reproduced sound. In the figures,  $h$  is the interval between the acoustic radiation planes 332 and 333 (acoustic radiation plane interval).

Figures 35C and 35D show wider directional radiation patterns than those shown in Figures 35A and 35B. A broad directional radiation pattern is obtained when the acoustic radiation plane interval  $h$  is greater

than approximately  $1/2$  of the wavelength at the upper limit frequency in the frequency band which is desired to realized as a dipole characteristic. Accordingly, a narrow dipole directional radiation pattern can be obtained by setting the acoustic radiation plane interval  $h$  to approximately  $1/2$  or less of the wavelength at the upper limit frequency in the frequency band which is desired to be realized as a dipole characteristic.

10

With the on-vehicle acoustic reproducing apparatuses according to Embodiments 14 through 23 of the present invention, a desirable sound environment can be achieved in which a sufficient volume of the reproducing sound is ensured along the acoustic radiation main axis of the sound source, while the amount of sound transferred directly from the sound source is reduced in the position of a passenger such as a driver. Moreover, it is possible to obtain a desirable directional radiation pattern by improving the variation in the characteristics of the loudspeakers of the dipole sound source and the variation in the characteristics of the non-directional sound source.

25

Furthermore, it is understood that the effects of the above-described on-vehicle amplification-sound apparatus of the present invention can be obtained similarly with an amplification-sound apparatus having the structure as described in, for example, Embodiments 1 through 13 of the present invention.

30

Embodiment 24

09486864-060800



As Embodiment 24 of the present invention, a method for controlling an amplitude of an amplification-sound apparatus will now be described with reference to Figure 36 to 39C. The method is performed by appropriately controlling the phase difference between the radiated sound from an amplified sound source (amplification-sound) and the radiated sound from a control sound source (control sound) in view of the wavelength at the control frequency.

10

Each of Figures 36 and 38 is a schematic diagram illustrating the planar extension of the radiated sound from each of the amplified sound source 401 and the control sound source 403 at a frequency to be controlled (control frequency). Each of Figures 37A to 37C and 39A to 39C is a cross-sectional view illustrating the extension of the radiated sound from each of the amplified sound source 401 and the control sound source 403 at the control frequency, while also illustrating therein the amplified sound source 401 and the control sound source 403. A point a shows a control point at which the radiated sound is controlled, and each of the figures shows a case where the control point a is set along a straight line between the amplified sound source 401 and the control sound source 403. Furthermore, Figures 36 and 37A to 37C show a case where an interval d between the amplified sound source 401 and the control sound source 403 is  $1/4$  of the wavelength  $\lambda$  of the control frequency (i.e.,  $d=\lambda/4$ ). Figures 38, 39A to 39C show a case where an interval d between the amplified sound source 401 and the control sound source 403 is  $1/2$  of the wavelength  $\lambda$  of the control frequency (i.e.,  $d=\lambda/4$ ).

In Figures 36 and 38, b1 is a line indicating a peak of the waveform of the amplified sound, c1 is a line indicating a dip of the waveform of the control sound, e shows a main axis direction of the acoustic radiation. On the other hand, in Figures 37A to 37C and 39A to 39C, b2 is the waveform of the amplified sound, c2 is the waveform of the control sound, f is the waveform which is produced by interference between the amplified sound b2 and the control sound c2.

When the amplified sound source 401 and the control sound source 403 can be considered as point sound sources, respectively, the lines b1 and c1 are represented as shown as circles having the sound sources for their central points, respectively. The control sound is controlled so as to be interfere with, and canceled out by, the amplified sound at the control point a, and then radiated from the control sound source 403. Thus, when the waveform of the amplified sound is in its peak at the control point a, the waveform of the control sound is in its dip at the control point a. Therefore, as shown in Figures 36 and 38, the peak b1 of the amplified sound and the dip c1 of the control sound meet at the control point a.

As schematically illustrated in Figures 37A to 37C and 39A to 39C, the frequencies of the amplified sound b2 and the control sound c2 which are interfered with, and canceled out by, each other at the control point a coincide with each other. Thus, if the control sound c2 is controlled to be in its dip at control point a when the amplified sound b2 is in its peak at

the control point a (see Figures 37A and 39A) so as to cancel out the amplified sound b2 by interference at the control point a, practically, as shown by the waveform f in Figures 37C and 39C, the amplified sound b2 is canceled out not only at the control point a but also at other points beyond the control point a.

When the amplified sound source 401 and the control sound source 403 can be considered as point sound sources, by setting the interval d between the sound sources to approximately  $1/4$  ( $d=\lambda/4$ ) of the wavelength of the control wavelength  $\lambda$ , it is possible to amplify the amplified sound b2 as shown by the waveform f in Figure 37C by means of interference between the amplified sound b2 (see Figure 37A) and the control sound c2 (see Figure 37B) along the main axis direction of the acoustic radiation e. On the other hand, by setting the interval d between the amplified sound source 401 and the control sound source 403 to approximately  $1/2$  ( $d=\lambda/2$ ) of the wavelength of the control wavelength  $\lambda$ , the amplified sound b2 is canceled out not only at the control point a but also along the main axis direction of the acoustic radiation e as shown by the waveform f in Figure 39C by means of interference between the amplified sound b2 (see Figure 39A) and the control sound c2 (see Figure 39B).

Therefore, with the arrangement described above in which the interval d between the amplified sound source 401 and the control sound source 403 to approximately  $1/4$  ( $d=\lambda/4$ ) of the wavelength of the

00486864-060800

control wavelength  $\lambda$ , the amplified sound b2 can be canceled out at the control point a, while it is amplified along the main axis direction of the acoustic radiation e by interference between the amplified sound b2 and the control sound c2.

In the above description, the control point a is located along the straight line between the amplified sound source 401 and the control sound source 403. However, even when the control point a is not along such a line, if the sound source interval d is controlled in the same manner, it is also possible to cancel out the amplified sound b2 at the control point a while amplifying the amplified sound b2 along the main axis direction of the acoustic radiation e by interference between the amplified sound b2 and the control sound c2.

Even when the amplified sound source 401 and the control sound source 403 are not point sound sources, substantially the same effects as described above can be obtained by setting the path difference of the radiation sound from each of the sound source 401 and 403 to the control point a to approximately  $1/4$  of the wavelength of the control frequency  $\lambda$ .

Further, it is possible to combine the above-described method as Embodiment 24 of the present invention with any other appropriate structure previously described in Embodiments 1 to 23.

The amplification-sound apparatus of the present invention described above is applicable to various

09486864-060800

applications in which an output of an amplified sound having a predetermined directionality is desired. Although an on-vehicle amplification-sound apparatus has been described as one particular example of an application of the present invention, the application of the present invention is of course not limited to these examples.

#### INDUSTRIAL APPLICABILITY

10 As described above, according to the amplification-sound apparatus of the present invention, a predetermined directional radiation pattern can be realized by providing a control sound source in the vicinity of the amplified sound source. When the

15 amplified sound source and the control sound source are provided as a horn loudspeaker which includes a horn driver and an acoustic tube, an even more desirable directional radiation pattern and acoustic characteristic can be realized with respect to an

20 externally radiated sound. If the acoustic tube is provided as a reentrant horn, a small-size amplification-sound apparatus is realized.

25 According to the amplification-sound apparatus of the present invention which is described as a directional loudspeaker, a sharp directional radiation pattern based on a reflector can be realized by reducing an amplified sound radiated from the back of the sound source.

30 Furthermore, according to the on-vehicle acoustic reproducing apparatus of the present invention which is implemented by applying an amplification-sound

apparatus of the present invention to an on-vehicle use, a sufficient volume of sound is ensured in the axis direction of the acoustic radiation of the sound source, while reducing the amount of sound transferred directly from the sound source in the position of a passenger such as a driver, thereby obtaining a desirable sound environment. An excellent directional radiation pattern can be also achieved by improving the variation in the characteristics of loudspeakers of a dipole sound source and/or a non-directional sound source.

According to the present invention, the phase difference between the radiated sound from an amplified sound source (amplified-sound) and the radiated sound from a control sound source (control sound) are appropriately controlled in view of a wavelength of a control frequency, whereby an amplitude of the amplified sound can be controlled. Specifically, when the interval between the amplified sound source and the control sound source is set to approximately  $1/4$  of the wavelength of the control wavelength, the amplified sound can be canceled out at the control point, while the amplified sound is amplified along the main axis direction of the acoustic radiation by interference between the amplified sound and the control sound.

008090"49898460

## CLAIMS

1. A sound-amplification apparatus, comprising:

```

        an acoustic signal source for outputting an
5  acoustic signal;

```

an amplified sound source for receiving the acoustic signal from the acoustic signal source and radiating an amplified sound;

10           a control sound source provided in a vicinity of  
the amplified sound source for radiating a control  
sound; and

signal processing means for producing a control sound signal by controlling at least one of an amplitude and a phase of the acoustic signal from the acoustic signal source so that an acoustic space having a desired directionality is formed by interference between the amplified sound and the control sound, and providing the control sound signal to the control sound source.

20           2. A sound-amplification apparatus according to claim 1,  
the signal processing means comprising:

an error detector provided in a vicinity of the control sound source for detecting a synthesized sound between the amplified sound and the control sound;

directional radiation pattern selection means  
for selecting one of an output from the error detector  
and the acoustic signal from the acoustic signal source  
so as to obtain a predetermined directional radiation  
pattern; and

calculation means for producing the control sound signal by using the signal selected by the directional radiation pattern selection means, and

providing the control sound signal to the control sound source, wherein the calculation means is provided for:

when ensuring a directionality such that the amplified sound directed toward the error detector is reduced, producing, as a first control sound signal, a signal obtained by controlling the amplitude and the phase of the acoustic signal from the acoustic signal source so that the output signal from the error detector is 0;

10           when ensuring a dipole directional radiation  
pattern, producing, as a second control sound signal, a  
signal obtained by inverting the phase of the acoustic  
signal from the acoustic signal source;

when ensuring a non-directional radiation  
15 pattern, producing, as a third control sound signal, a  
signal having a same phase as that of the acoustic  
signal from the acoustic signal source; and

providing one of the first to third control  
sound signals to the control sound source as the  
20 control sound signal.

3. A sound-amplification apparatus according to claim 1,  
wherein the control sound source is provided along a  
same axis with the amplified sound source so that an  
acoustic radiation plane thereof is located  
symmetrically with an acoustic radiation plane of the  
amplified sound source.

4. A sound-amplification apparatus according to claim 2,  
30 wherein the error detector is provided along a straight  
line which passes through respective centers of the  
acoustic radiation planes of the amplified sound source  
and the control sound source.



5. A sound-amplification apparatus according to claim 2, the calculation means comprising:

5 a filtered-X filter for, where a transfer function of a space extending from the control sound source to the error detector is denoted by C, multiplying the acoustic signal output from the acoustic signal source by the transfer function C;

10 an adaptive filter for performing a convolution calculation on the acoustic signal from the acoustic signal source with a transfer function F, and providing the obtained calculation result to the control sound source as the first control sound signal; and

15 a coefficient updatator for receiving an output from the directional radiation pattern selection means as an error signal, receiving an output from the filtered-X filter as a reference signal, updating a coefficient of the adaptive filter so that the error signal is small, and optimizing the transfer function F.

20

6. A sound-amplification apparatus according to claim 1, the amplified sound source comprising:

25 a horn driver for converting the acoustic signal from the acoustic signal source to an aerial vibration; and

a horn-shaped acoustic tube for continuously enlarging a wavefront of the aerial vibration output from the horn driver along a sound wave traveling direction.

30

7. A sound-amplification apparatus according to claim 1, the control sound source comprising:

a horn driver for converting the control sound

09486864-060800

signal output from the signal processing means to an aerial vibration; and

5 a horn-shaped acoustic tube for continuously enlarging a wavefront of the aerial vibration output from the horn driver along a sound wave traveling direction.

10 8. A sound-amplification apparatus according to claim 6, wherein the acoustic tube includes a horn which is folded back at least once.

15 9. A sound-amplification apparatus according to claim 8, wherein the number of times the acoustic tube is folded back is an odd number.

20 10. A sound-amplification apparatus according to claim 7, wherein the acoustic tube includes a horn which is folded back at least once.

25 11. A sound-amplification apparatus according to claim 10, wherein the number of times the acoustic tube is folded back is an odd number.

30 12. A sound-amplification apparatus, comprising:  
a concave reflector; and  
a sound source provided within the reflector so as to be unidirectional toward a center of the reflector.

13. A sound-amplification apparatus according to claim 12, wherein

the sound source includes a control sound source for outputting a control sound and an amplified sound

008090"49898460

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

[illegible][illegible][illegible][illegible][illegible]

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

[illegible]

so that the error signal is small, and optimizing the transfer function F.

5 15. A sound-amplification apparatus according to  
claim 13, further comprising signal correction means  
for performing at least one of a delay control, an  
amplitude control and a phase control on the acoustic  
signal output from the acoustic signal source, and  
10 providing a resultant signal to the amplified sound  
source.

16. A sound-amplification apparatus according to  
claim 15, the signal processing means comprising:  
15 an error detector provided in a radiation space  
of the control sound from the control sound source for  
detecting a synthesized sound between the amplified  
sound and the control sound;

20 a filtered-X filter for, where a transfer  
function of an acoustic space extending from the  
control sound source to the error detector is denoted  
by C, multiplying the acoustic signal output from the  
acoustic signal source by the transfer function C;

25 an adaptive filter for performing a convolution  
calculation on the acoustic signal from the acoustic  
signal source with a transfer function F, and providing  
the calculation result to the control sound source as  
the control sound signal; and

30 a coefficient updator for receiving an output  
from the error detector as an error signal, receiving  
an output from the FX filter as a reference signal,  
updating a coefficient of the adaptive filter so that  
the error signal is small, and optimizing the transfer  
function F, wherein

09486864-060800

where the delay control is performed, the signal correction means performs the delay control with a delay time which corresponds to an amount of time required for the control sound radiated from the control sound source to reach the error detector.

17. A sound-amplification apparatus according to claim 16, wherein the transfer function  $F$  of the adaptive filter is expressed as  $-G/C$ , where  $G$  denotes an acoustic transfer function from the amplified sound source to the error detector.

18. A sound-amplification apparatus according to claim 13, wherein the control sound source is provided along a same axis with the amplified sound source so that an acoustic radiation plane thereof is located symmetrically with an acoustic radiation plane of the amplified sound source.

19. A sound-amplification apparatus according to claim 14, wherein the error detector is provided along a straight line which passes through respective centers of the acoustic radiation plane of the amplified sound source and the control sound source.

20. A sound-amplification apparatus according to claim 16, wherein the error detector is provided along a straight line which passes through respective centers of the acoustic radiation plane of the amplified sound source and the control sound source.

21. An on-vehicle sound-amplification apparatus, comprising:

09486364-060800

a dipole sound source provided in a vicinity of a position of a passenger wherein at least one acoustic radiation axis thereof is directed outwardly from a vehicle interior; and

5           signal processing means for amplifying an acoustic signal and then inputting an output thereof to the dipole sound source.

10       22. An on-vehicle sound-amplification apparatus according to claim 21, further comprising:

15           a non-directional sound source provided in a vicinity of a center of the dipole sound source wherein an acoustic radiation thereof is driven to have an inverted phase from that of the acoustic radiation of the dipole sound source which is directed into the vehicle interior, wherein

          the output from the signal processing means is also input to the non-directional sound source.

20       23. An on-vehicle sound-amplification apparatus according to claim 21, wherein:

25           the dipole sound source includes at least two loudspeakers wherein the at least two loudspeakers are arranged so that respective acoustic radiation planes thereof are directed opposite to each other; and

          the signal processing means variably controls a phase of an input to at least one of the loudspeakers included in the dipole sound source.

30       24. An on-vehicle sound-amplification apparatus according to claim 23, wherein: each of the at least two loudspeakers included in the dipole sound source has an acoustic tube whose cross-sectional area along a

004486864-060800

direction perpendicular to a sound wave traveling direction varies continuously; the acoustic tubes of the respective loudspeakers are arranged so that respective acoustic radiation planes thereof are directed opposite to each other; and a radiated sound from the loudspeaker which is driven by an output from the signal processing means is radiated by being guided along the acoustic tube.

10 25. An on-vehicle sound-amplification apparatus  
according to claim 23, the signal processing means  
comprising:

15           a radiation sound detector provided in a vicinity of a first one of the at least two loudspeakers included in the dipole sound source;

an error detector provided in a vicinity of a second one of the loudspeakers included in the dipole sound source;

an adder for adding together respective outputs  
20 from the radiated sound detector and the error  
detector; and

calculation means for receiving the acoustic signal and the output from the adder, performing a calculation so that the output from the adder is small, and inputting the obtained result to the second  
25 loudspeaker located in the vicinity of the error detector, wherein

the acoustic signal is input to the first  
loudspeaker located in the vicinity of the radiated  
30 sound detector.

26. An on-vehicle sound-amplification apparatus according to claim 25, the calculation means

comprising:

an adaptive filter for receiving the acoustic signal;

a filter for receiving the acoustic signal; and

5 a coefficient updatator for receiving the output from the adder and an output from the filter, wherein:

an output from the adaptive filter is input to the second loudspeaker located in the vicinity of the error detector;

10 the coefficient updatator updates a coefficient of the adaptive filter by performing a calculation so that the output from the adder is small; and

the filter has a characteristic equal to a transfer function from the error detector to the second loudspeaker located in the vicinity of the error detector.

27. An on-vehicle sound-amplification apparatus according to claim 23, the signal processing means comprising:

a radiated sound detector arranged in a vicinity of a first one of the at least two loudspeakers included in the dipole sound source;

25 a first error detector arranged in a vicinity of a second one of the loudspeakers included in the dipole sound source;

a second error detector arranged in a vicinity of the non-directional sound source;

30 signal correction means for receiving an output from the second error detector;

a first adder for adding together an output from the radiation sound detector and an output from the first error detector;

008090"4998450



a second adder for adding together the output from the first error detector and an output from the signal correction means;

5 first calculation means for receiving the acoustic signal and an output signal from the first adder, and performing a calculation so that the output signal from the first adder is small, wherein an output therefrom is input to the second loudspeaker located in the vicinity of the first error detector; and

10 second calculation means for receiving the acoustic signal and an output signal from the second adder, and performing a calculation so that the output signal from the second adder is small, wherein an output therefrom is input to the non-directional sound source, wherein

15 the acoustic signal is input to the first loudspeaker located in the vicinity of the radiation sound detector.

20 28. An on-vehicle sound-amplification apparatus according to claim 27, the first calculation means comprising:

a first adaptive filter for receiving the acoustic signal;

25 a first filter for receiving the acoustic signal; and

a first coefficient updatator for receiving the output from the first adder and an output from the first filter, wherein:

30 an output from the first adaptive filter is input to the second loudspeaker located in the vicinity of the first error detector;

the first coefficient updatator updates a

09483864-060800

coefficient of the first adaptive filter by performing a calculation so that the output from the first adder is small; and

5 the first filter has a characteristic equal to a transfer function from the first error detector to the second loudspeaker located in the vicinity of the first error detector, the second calculation means comprising:

10 a second adaptive filter for receiving the acoustic signal;

a second filter for receiving the acoustic signal; and

15 a second coefficient updator for receiving the output from the second adder and an output from the second filter, wherein:

an output from the second adaptive filter is input to the non-directional sound source;

20 the second coefficient updator updates a coefficient of the second adaptive filter by performing a calculation so that the output from the second adder is small; and

the second filter has a characteristic equal to a transfer function from the second error detector to the non-directional sound source.

25 29. An on-vehicle sound-amplification apparatus according to claim 24, wherein the acoustic tube of each of the at least two loudspeakers included in the dipole sound source is formed of a sound path having a  
30 desired bent shape.

30. An on-vehicle sound-amplification apparatus according to claim 29, wherein the at least two

009090-4933450

loudspeakers included in the dipole sound source are arranged so that an interval between the respective acoustic radiation planes included in the acoustic tubes of the loudspeakers is less than or equal to approximately 1/2 of the wavelength of the reproduced sound.

31. A sound-amplification apparatus according to claim 1, wherein an acoustic radiation plane of the amplification-sound source and an acoustic radiation plane of the control sound source are placed such that a difference between a phase of the amplified sound and a phase of the control sound at a desired frequency is substantially within 90° in a direction along a main axis of acoustic radiation of the amplified sound.

32. A sound-amplification apparatus according to claim 13, wherein an acoustic radiation plane of the amplification-sound source and an acoustic radiation plane of the control sound source are placed such that a difference between a phase of the amplified sound and a phase of the control sound at a desired frequency is substantially within 90° in a direction along a main axis of acoustic radiation of the amplified sound.

33. An on-vehicle sound-amplification apparatus according to claim 21, the dipole sound source comprising an amplified sound source for radiating an amplified sound and a control sound source for radiating a control sound, wherein


an acoustic radiation plane of the amplification-sound source and an acoustic radiation plane of the control sound source are placed such that


a difference between a phase of the amplified sound and a phase of the control sound at a desired frequency is substantially within  $90^\circ$  in a direction along a main axis of acoustic radiation of the amplified sound.

## ABSTRACT

A sound-amplification apparatus comprises: an acoustic signal source for outputting an acoustic signal; an amplified sound source for receiving the acoustic signal from the acoustic signal source and radiating an amplified sound; a control sound source provided in a vicinity of the amplified sound source for radiating a control sound; and signal processing means for producing a control sound signal by controlling at least one of an amplitude and a phase of the acoustic signal from the acoustic signal source so that an acoustic space having a desired directionality is formed by interference between the amplified sound and the control sound, and providing the control sound signal to the control sound source.


09433554-050800

**FIG. 1**




09486864-060300



3/28

*FIG. 3*




**FIG. 4**

5/28


**FIG. 5**100**FIG. 6**

6/28


**FIG. 7A** Output signal from  
acoustic signal source




**FIG. 7B** Output signal from  
error detector




**FIG. 7C** Output signal 1 from  
calculation means



**FIG. 7D** Output signal 2 from  
calculation means






**FIG. 7E** Output signal 3 from  
calculation means





09486864-06000


7/28

**FIG. 8****FIG. 9****FIG. 10**

8/28


**FIG. 11****FIG. 12**

9/28

**FIG. 13**


10/28

**FIG. 14**



09486864-06000

11/28

*FIG. 15*

09486864-050800



12/28


**FIG. 16**210

FIG. 17B




FIG. 17A




FIG. 17C




FIG. 18




FIG. 19




FIG. 20








FIG. 21



**FIG. 22**

17/28

**FIG. 23****FIG. 24**

18/28

FIG. 25




FIG. 26









FIG. 27




**FIG. 28A****FIG. 28B****FIG. 28C****FIG. 28D**




20/28

**FIG. 29**





340

**FIG. 30**




350

008090" 49898460

**FIG. 31****FIG. 32**

22/28


FIG. 33

380




**FIG. 35A**


Interval between acoustic  
radiation planes  
: Wavelength of  
reproduced sound  $\times (1/4)$

**FIG. 35B**


Interval between acoustic  
radiation planes  
: Wavelength of  
reproduced sound  $\times (1/2)$


**FIG. 35C**

Interval between acoustic  
radiation planes  
: Wavelength of  
reproduced sound  $\times (2/3)$




**FIG. 35D**

Interval between acoustic  
radiation planes  
: Wavelength of  
reproduced sound  $\times (8/9)$




**FIG. 36**

26/28




*FIG. 37A**FIG. 37B**FIG. 37C*

09/486864-060800

27/28





**FIG. 39A****FIG. 39B****FIG. 39C**

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032  
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

<b>DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)</b>	<b>Attorney Docket Number</b>	28569.5100	
	<b>First Named Inventor</b>	Isao KAKUHARI	
	<b>COMPLETE IF KNOWN</b>		
	<b>Application Number</b>	09/486,864	
	<b>Filing Date</b>	March 2, 2000	
	<b>Group Art Unit</b>		
<input type="checkbox"/> Declaration Submitted with Initial Filing	<input checked="" type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	<b>Examiner Name</b>	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

SOUND-AMPLIFICATION APPARATUS

the specification of which

(Title of the Invention)

☐ is attached hereto  
OR

☒ was filed on (MM/DD/YYYY) 03/02/2000 as United States Application Number or PCT International

Application Number 09/486,864 and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
8-072177	Japan	03/27/1996	<input checked="" type="checkbox"/>	YES	NO
9-291266	Japan	10/23/1997	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
9-291265	Japan	10/23/1997	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
PCT/JP98/04471	PCT	10/02/1998	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

(July 1998)

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)  
Approved for use through 9/30/00: OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

## DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
PCT/JP98/04471	10/02/1998	

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: ☒ Customer Number 20322 → ☐ Registered practitioner(s) name/registration number listed below

Place Customer  
Number Bar Code  
Label here

Name	Registration Number	Name	Registration Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☒ Customer Number 20322 OR ☐ Correspondence address below

Name					
Address					
Address					
City		State		ZIP	
Country		Telephone		Fax	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:		<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])		Family Name or Surname			
Isao		KAKUHARI			
Inventor's Signature	<i>Isao Kakuhari</i>			Date	5/29/00
Residence: City	Nara	State		Country	Japan
Post Office Address	2-1-2, Shikanodainishi, Ikoma-shi				
Post Office Address					
City	Nara	State		ZIP	630-0114
				Country	JAPAN

☒ Additional inventors are being named on the 1 supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → +

PTO/SB/02A (3-97)  
Approved for use through 9/30/98. OMB 0651-0032  
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

+

<b>DECLARATION</b>	<b>ADDITIONAL INVENTOR(S)</b> Supplemental Sheet Page <u>1</u> of <u>1</u>
--------------------	----------------------------------------------------------------------------------

00483664-0000

<b>Name of Additional Joint Inventor, if any:</b>				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Kenichi				TERAI			
Inventor's Signature	Kenichi Terai					Date	5/29/00
Residence: City	Osaka	State		Country	Japan JPX	Citizenship	Japan
Post Office Address 5-10-10, Taharadai, Shijonawate-shi,							
Post Office Address							
City	Osaka	State		ZIP	575-0013	Country	Japan
<b>Name of Additional Joint Inventor, if any:</b>				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Hiroyuki				HASHIMOTO			
Inventor's Signature	Hiroyuki Hashimoto					Date	5/29/00
Residence: City	Osaka	State		Country	Japan JPX	Citizenship	Japan
Post Office Address 1-7-18, Morofuku, Daito-shi							
Post Office Address							
City	Osaka	State		ZIP	574-0044	Country	Japan
<b>Name of Additional Joint Inventor, if any:</b>				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Inventor's Signature						Date	
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		ZIP		Country	

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

+

**Burden Hour Statement:** This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. **DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.**